

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3528)

-----  
Set a basalt stone, 14x10x8", 10" in the ground for ¼ sec. cor., marked ¼ on N face, from which

A fir, 8" dia., bears S.10°E., 41 lks., mkd: ¼ S11 BT.

A fir, 7" dia., bears N.15°W., 15 lks., mkd: ¼ S2 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - Nov. 29, 1966 - C.S. File 52/30-68

-----  
Found - Orig Basalt Corner Stone, 14x10x8" mkd "¼" on N Face  
Orig. 7" now 9" Fir, N.15°W. 9.9 ft., prev, opened & shows "S" pocket knife-type scribe. Open lower & find "BT" done in the same manner. Under 66 years growth.

Orig. S.E. BT now only rotted remains, possible reverse scribe.

Set brass Cap at Cor. Mkd: County Surveyors T25S ¼  $\frac{S}{S 11}$  R1W  
(Reset Rock alongside) Office, 1966

New BTs- 8" R.Cedar N.39°W., 27.7 ft. mkd. ¼ S2 CS BT.

8" R.Cedar S.48°E., 35.2 ft. mkd. ¼ S11 CS BT.

Note - This corner lies on nearly flat bench, approx. 200 ft E of new logging road, course N-S.

-----  
4/26/72-Reset Brass Cap & Rock, 3 BTs O.K. V.R.T.)