

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; & 35, T24-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2782)

-----  
Set a basalt stone 12x8x8 ins., 8" in the ground, for 1/4 sec. cor. mkd. 1/4 on N. face, from which

A Fir 60" dia., bears N.50°E., 35 lks. dist. mkd. 1/4 S BT

A Fir 20" dia., bears S.5°E., 11 lks. dist. mkd. 1/4 S BT.

Cor. is on a hillside, sloping SW. 50 ft. above McKinley Ck.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - June 4, 1963 - C.S. 52/30-15

-----  
Found - At corner, Rock mkd. "1/4S" on N. face as called for in Govt. notes.

60" Fir, N.50°E., 23.1 ft. shows good scar, did not open.

24" Fir S.5°E., 7.3 ft., shows good scar, did not open.

Alongside rock, Set brass cap mkd. County Surveyors Office

T24S R1W 1/4 S 35  
T25S S 2

1963

New BTs- 9" R.Cedar N.53°W., 10.1 ft. mkd. 1/4 S35 CS BT.

18" Red Cedar S.77°E., 15.0 ft. mkd. 1/4 S2 CS BT.

Adam DeGroot - For: Seneca Jones Timber Co. - July 2020 - M177-19

-----  
Found - A 1 1/2" Iron post by DCSO in 1963 per CS 52/30, firmly set and projecting 12" above the ground, with original stone loose against south side, with a 2 1/2" brass cap (properly) marked:

From which the original BTs by Nicklin in 1896 -

A 60" D.Fir bears N.47°15'E., 22.9 ft w/healed blaze (N.50°E., 35 lks) (N.50°E., 23.1') 1963

A 36" D.Fir bears S.4°45'E., 7.7 ft w/healed blaze (S.5°E., 11 lks) (S.5°E., 7.3') 1963

BTs by DCSO in 1963 -

A 26" Cedar bears S.77°15'E., 15.0 ft w/healed blaze (S.77°E., 15.0')

A 14" Cedar bears N.53°30'W., 10.3 ft w/healed blaze (N.53°W., 10.1')

Lat: 43°26'14.65795"N Long: 122°46'14.91493"W