

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias	Description

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3507)

The point for ¼ sec. cor, falls on exposed bedrock, on which I cut a cross (+) at the exact cor. point for ¼ sec. cor marked ¼ on W side of cross, from which

- A Fir, 36" dia., bears S.88°E., 52 lks. mkd: ¼ S36 BT.
- A Fir, 28" dia., bears N.88°W., 49 lks. mkd ¼ S35 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Oct. 1966 - C.S. File 52/30-30

Found - Basalt outcrop 30"x12"x6" above ground, very solid and mkd. with "X" & "¼" on Top

- Orig. 36" now 42" Fir S.88°E., 34.3 ft.(face), shows good scar. Alive, we do not open
- Orig. 28" now 28" Fir Stub, N.88°W., 32.3 ft.(face), dead, shows "¼ S35" scribe on prev. opened blaze.

Set - Brass Cap at Cor. mkd: County Surveyors T25S R1W (alongside mkd. stone Office, 1966 ¼ S35|S36 & 1' south)

New BTs- 10" D.Fir S.86°E., 24.8 ft. mkd. ¼ S36 CS BT.
8" D.Fir S.65°W., 18.2 ft. mkd. ¼ S35 CS BT.

Note- This corner lies on S. slope, approx. 475 ft. N. of old Scared Man Trail.

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor under Group #1828, surveyed June/July 1997 - (DCSO records Vol. 53 Page(s) 20318)

Beginning at the ¼ sec. cor. of secs. 35 & 36, perpetuated by Tracy, in 1966, monumented with an iron post, 1½" dia., firmly set, projecting 8" above a mound of stone, 3 ft. base, 2 ft. high, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A sawed fir stump, 46" dia., bears N.88½°E., 55 lks., with healed blaze. (Record, S.88°E., 52 lks.)
- A partially decayed fir snag, 22" dia., bears West, 51 lks., with healed blaze. (Record, N.88°W., 49 lks.)

and bearing trees mkd. by Tracy

- A fir, 12" dia., bears S.86°E., 37½ lks., with healed double blazes.
- A fir, 11" diam., bears S.65°W., 27½ lks., with healed double blazes.