

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3507)  
-----  
A Hemlock, 5" dia., for cor. of secs. 25, 26, 35 & 36 I mark:  
T 25 S S 25 on NE.  
R 1 W S 38 on SE.  
S 35 on SW and  
S 26 on NW sides, with 1 notch on N and E sides,  
from which  
A Hemlock, 8" dia. bears N.89°E. 3 lks mkd T25S R1W S25 BT  
A Hemlock, 12" dia., bears S.51°E., 22 lks. mkd T25S R1W S36 BT.  
A Hemlock, 8" dia., bears S.80°W., 41 lks. mkd T25S R1W S35 BT.  
A Chinquapin, 8" dia., bears N.40°W., 14 lks. mkd T25S R1W S26 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Oct. 1966 - C.S. File 52/30-29  
-----  
Found - Orig. 5" now 7" Hemlock corner tree, alive & in good condition, shows good scars at the base of tree. Do not open.  
Orig. 8" now 15" Hemlock N.89°E., 2.0 ft. shows good scar. Alive, do not open.  
Orig. 12" now 28" Hemlock S.51°E., 14.5 ft. now stump shows "S 36" scribe on prev. opened blaze. No trace of NW nor SW BT.  
DO NOT SET BRASS CAP  
Set - 1/2" x 30" I. Rod at base of corner tree, NW side.  
14" D.Fir S.41°E., 50.4 ft. mkd: T25S R1W S36 CS BT.  
14" D.Fir S.6°W., 45.1 ft. mkd: T25S R1W S35 CS BT.  
11" Chinq. N.82°W., 67.6 ft. mkd: T25S R1W S26 CS BT  
Note - This corner lies on very steep N slope of hill.

Douglas Co. Surveyors Office - Gary Langlitz - P. Earle - 3/29/1974 - C.S. File 56/49-9  
-----  
Found - Corner tree with iron rod at base & BT as noted in 1966 with one exception, the 14" D.Fir BT to the SW marked in 1966 is now down.  
New BT - 11" Hemlock, bears N.44°E., 42.2 ft. scribed "T25S R1W S25 CS BT"

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16364)

-----  
The cor. of secs. 25, 26, 35, and 36, perpetuated & recorded by Tracy, in 1966, & further perpetuated by Langlitz, in 1974, monumented with the orig. corner tree, a hemlock, 8 ins. diam., with healed blaze on N., S., E., and W. faces, from which the remains of the original bearing trees:

A hemlock, 17" dia., bears N.89°E., 3 lks. with fragmentary scribe marks visible on open blaze.

A hemlock root crown, size indeterminate, bears S.51°E., 22 lks.

and the remains of bearing trees mkd. by Tracy

A fir, 16" dia., bears S.41°E., 74 lks. with fragmentary scribe marks visible on open blaze.

A chinquapin stump, 11" dia., bears N.83¼°W., 102½ lks. with scribe marks T25S R1W S26 CS BT visible on open blaze.

and a bearing tree mkd. by Langlitz

A hemlock, 12" dia. bears N.51°E. 63 lks. with fragmentary scribe marks visible on open blaze.

and a reference monument and a new bearing tree

An iron post, 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears S.68°W., 27 lks., with brass cap mkd. T25S R1W S35 RM 1978 and an arrow pointing to the corner.

A hemlock, 6" dia., bears N.25½°W., 25 lks., mkd. T25S R1W S26 BT.

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor under Group #1828, surveyed June/July 1997 - (DCSO records Vol. 53 Page(s) 20320)

-----  
The cor. of secs. 25, 26, 35 & 36, monumented with the orig. cor. tree, a hemlock, 13" dia., with healed blaze on the N. side, from which the remains of the original bearing trees:

A hemlock, 20" dia., bears N.89°E., 3 lks., with scribe marks R1W visible on opened blaze.

A decayed hemlock stump, size indeterminate, bears S.51°E., 22 lks., no marks visible.

and the remains of accessories mkd. by Tracy, in 1966

A fir, 18" dia., bears S.41°E., 74 lks., with healed double blazes.

An iron rod, 5/8" dia., firmly set, projecting 3" above ground, partially grown into the cor. tree, bears N.4½°W., 1 lk.

continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Langlitz, in 1974  
A hemlock, 14" dia. bears N.51°E. 63 lks. with fragmentary scribe mks. visible on partially healed blaze.  
and accessories mkd. by Jelley  
A iron post, 2½" dia., firmly set, projecting 2" above ground, bears S.66¾°W., 27 lks., with brass cap mkd. RM T25S R1W S35 1978 and an arrow pointing to the cor. (Record, S.68°W.)  
A hemlock, 11" dia., bears N.25½°W., 25 lks., with healed blaze.  
and new accessories  
A fir, 6" dia. bears S.77¾°W. 87 lks. mkd. T25S R1W S35 BT  
A stainless steel post, 28" long, 2½" dia., set 26" in the ground for a reference monument, bears N.82¾°W., 9.1 lks., with brass cap mkd. RM S26 6.0 FT TO COR 1997 and an arrow pointing to the cor.

Fd. as per 1997 BLM resurvey by D. Edwards 8/2012 - M164-1