

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3509)</p> <p>-----</p> <p>A Fir, 12" dia., for ¼ sec. cor., I mark ¼ S26 on W and S25 on E sides from which</p> <p> A Fir, 10" dia., bears N.78°E., 32 lks. mkd ¼ S25 BT.</p> <p> A Vine maple, 4" dia., bears N.66°W., 8 lks. mkd ¼ S26 BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Nov. 1966 - C.S. File 52/30-34</p> <p>-----</p> <p>Found - Orig. 12", now 13" Corner Tree Alive. Chopped open & shows "¼S" scribe on W. face.</p> <p> Orig. 10", now 9" Fir N.78°E., 14.1 ft. (not 21.1 ft. prob. 10 lk. error in orig. meas.) chopped open & shows "¼S BT" scribe, now Snag.</p> <p> Vine Maple Sprouts N.66°W. 5.3 ft., locus of NW orig. BT.</p> <p>Set - Brass Cap at Cor Mkd: County Surveyors T25S ¼ S26/S25 R1W at base of Corner Tree Office, 1966 on North Side.</p> <p>New BTs- 26" D. Fir S.71°W., 20.8 ft. mkd. ¼ S26 CS BT.</p> <p> 7" Hemlock S.36°E. 5.6 ft. mkd. ¼ S25 CS BT.</p> <p>Note - This corner lies on steep East slope.</p>
<p>Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-50</p> <p>-----</p> <p>Found - 1966 DCSO 2½" brass cap on iron pipe</p> <p>BTs - 16" Hemlock, bears S.36°E., 5.6 ft "healed face"</p> <p> 52" D.Fir, bears S.71°W., 20.6 ft "healed face"</p>