

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3509-10)  
-----  
Set a basalt stone, 18x8x6", 12" in the ground for cor. of secs. 23, 24, 25, & 26, & marked with 2 notches on S & 1 notch on E edges, from which  
A fir 10" dia. bears N.35°E., 19 lks. mkd: T25S R1W S24 BT  
A hemlock, 5" dia., bears S.43°E., 11 lks., mkd: T25S R1W S25 BT.  
A hemlock, 5" dia., bears S.75°W., 15 lks., mkd: T25S R1W S26 BT.  
A hemlock, 6" dia., bears N.61°W., 22 lks., mkd: T25S R1W S23 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, Chainman - Oct. 1962 - C.S. File 52/30-13  
-----  
Found - ¾" Iron Reinforcing Rod, no record.  
Did not find rock called for in Gov't Notes  
All Orig. BTs alive & standing vis:  
5" Hemlock, now 8", S.75°W. 9.9 ft. Prev. opened & scribing vis.  
6" Hemlock, now 8", N.61°W. 14.5 ft. shows good scar  
5" Hemlock, now 5", S.43°E. 7.3 ft. shows good scar.  
10" W.Fir, now 17", N.35°E. 12.5 ft., shows 2 good scars.  
Corner & BT's. in good condition. Corner lies on E. slope approx. 150 ft. West of S end of bridge on Canton Creek Road. This corner found by Godfrey and Crew & everything checked so is a good corner but never has been recorded.

Thomas E. Shrum, Jr. by U.S. Plywood Corp. - Jan. 1963 - C.S. File 51/254-2  
-----  
Found - Original Stone (broken)  
18" D.Fir, N.35°E., 12.5 ft.  
6" Hemlock, S.43°E., 7.3 ft.  
10" Hemlock, S.75°W., 9.9 ft.  
11" Hemlock, N.61°W. 14.5 ft.  
Set - 2½" Aluminum Cap.

Fd. Ok by DCSO V.R. Tracy - 10/1962 - C.S. file 52/30-34A

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-50  
-----  
Found - 1963 USPC 2½" Alum cap on iron pipe  
BTs - 12" Hemlock, bears S.43°E., 7.2 ft "healed face"  
continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor Secs 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>28" D.Fir bears N.35°E., 12.5 ft "healed face" BTs (No record found)- 14" Hemlock bears N.63°E., 17.0 ft "healed face" 30" Cedar bears S.88°W., 28.5 ft "healed face"</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause &amp; Jeff Lorsung- 5/14/2024 - C.S. File 67/57-59 ----- Found - 1963 USPC 2½" alum cap (properly mkd) on IP, up 4". 9" hemlock S.43°E., 7.2 ft. fully healed double blaze, add 3½" mag nail right side center. 28" W.Fir (rec D.Fir) N.35°E., 12.5 ft. healed face, add 3½" mag nail right side center. 13" hemlock N.63°E., 17.0 ft. healed single blaze, add 3½" mag nail right side center. 28" I.Cedar S.88°W., 28.5 ft. partially healed single blaze T25S R1W S26 BT visible, add 3½" mag nail right side center. Note - Compass decl. 14½°E. Oregon Coordinate Reference System Cottage Grove - Canyonville Zone N 199369.107 E 316128.316</p>