

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3511)

-----  
Set a basalt stone, 18x9x8", 12" in the ground for ¼ sec. cor., marked ¼ on W face, from which

A Fir, 20" dia., bears N.53°E., 49 lks. mkd ¼ S24 BT.

A Fir, 6" dia., bears S.14°W., 25 lks. mkd ¼ S23 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Oct. 21 1966 - C.S. File 52/30-35

-----  
Found - Orig. Basalt Stone 17x5x9" mkd. "¼" on W. face, firmly set.

Orig. 20", now 30" Fir, N.53°E., 32.3 ft. Alive, shows very good scar. Do not open, but rescribe above old blaze: "¼ S23 CS BT"

Set Brass Cap at Cor. Mkd: County Surveyors T25S S23|S24 R1W Office 1966 Reset Rock alongside.

New BT - 7" D.Fir S.27°E., 12.0 ft. mkd. ¼ S24 CS BT.

Note - This corner lies on steep south slope changing to SW slope approx. 500 ft. north of Canton Creek Rd