

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3513-4)  
-----  
Set a basalt stone, 16x12x12", 11" in the ground for cor. of secs. 11, 12, 13 & 14, marked with 4 notches on S & 1 notch on E edges, from which  
A Fir, 13" dia. bears N.88°E. 31 lks. mkd "T25S R1W S12 BT  
A Rhododendron, 7" dia., bears S.53°E., 24 lks., mkd T25S R1W S13 BT.  
A Rhododendron, 16" dia., bears S.61°W., 23 lks., mkd T25S R1W S14 BT.  
A Fir, 15" dia. bears N.38½°W. 27 lks. mkd T25S R1W S11 BT

G. Robert Lecklider - For: U.S. Plywood Corp. - Aug. 1960 - M19-46  
-----  
Found - Corner stone  
13" Fir N.88°E., 20.5 ft.  
15" Fir N.38°W., 17.8 ft., dead.  
Stump hole - S.53°E.  
Set - 32" Fir S.60°W., 33.7 ft.  
30" Fir N.10°W., 42.0 ft.  
14" Fir S.36°E., 57.6 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Aug. 1966 - C.S. File 52/30-18  
-----  
Found - No trace of Basalt Stone called for in orig. notes. BTs all destroyed except one, a follows: 1960 30", now 31" D.Fir N.10°W., 42.0 ft., Alive shows S11 RE4079 BT".  
Set - Brass Cap mkd. County Surveyors T25S S 11|S 12 R1W  
Office, 1966 S 14|S 13  
New BTs- 20" I.Cedar N.40°W. 50.3 ft. mkd. T25S R1W S11 CS BT  
9" I.Cedar S.20°W. 39.7 ft. mkd. T25S R1W S14 CS BT  
(4 ft. off ground)  
No trees available to East due to logging.  
Corner lies on N-S cutting line, cut off to East.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1440, surveyed July/Aug 1988 - (DCSO records Vol. 49 Page(s) 18656-7)  
-----  
The cor. of sees. 11, 12, 13, & 14, perpetuated & recorded by Lecklider, in 1960, & further perpetuated & recorded by Tracy, in 1966; monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd. continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor Secs 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of original bearing trees  
A sawed fir stump, 18" dia. bears N.88°E., 31 lks., no marks visible.  
A root hole, bears N.38½°W., 27 lks. with down fir alongside, 18" dia., with scribe marks T25S R1W S11 visible on opened blaze.  
and the remains of BTs mkd. by Lecklider  
A root hole, bears S.60°W., 51 lks., with down fir alongside, 34" dia., with scribe marks 4079 visible on open double blaze.  
A fir, 35" dia., bears N.8°W., 66 lks., with scribe marks S11 RE 4079 BT visible on partially healed double blaze.  
and the remains of BTs mkd. by Tracy  
A root hole, bears S.20°W., 60 lks., with down cedar alongside, 12" dia., with scribe marks T25S R1W S14 CS BT visible on open double blaze.  
A cedar, 25" dia., bears N.41°W., 76 lks., with fragmentary scribe marks visible on partially healed double blaze.  
and new bearing trees  
A fir, 4" dia., bears N.45°E., 19 lks., mkd. X BT.  
A madrone, 12" dia., bears S.46½°E., 34 lks., mkd. T25S R1W S13 BT on the bark.  
A fir, 15" dia. bears S.60°W. 63 lks. mkd. T25S R1W S14 BT

Gerald Nygren - For: Sierra Pacific Industries - 6/2022 - M181-9

-----  
Condition report  
Found - 1966 County Surveyor brass cap  
BT (1900) 13" D.Fir, now 18" stump bears N.88°E., 20.46' healed blaze  
BT (1960) 30" D.Fir, now 39" bears N.8°W., 43.56' healed blaze rec. = N.10°W., 42.0'  
BT (1966) 20" Cedar, now 28" bears N.41°W., 50.16' healed blaze rec. = N.40°W, 50.3'  
BT (BLM 1988) 4" D.Fir, now 9" bears N.45°E., 12.54' healed blaze.  
BT (BLM 1988) 12" Madrone, now 24" bears S.46°30'E., 22.44' healed blaze  
BT (BLM 1988) 15" D.Fir, now 24" bears S.60°W., 41.58' healed blaze