

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO rec Vol. 8 Pg) 3500

-----  
Set a Fir post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S36 on N. and S1 on S. faces, from which  
A Fir 14" dia., bears S.86°E., 162 lks. mkd. ¼ S1 BT.  
A Fir 10" dia., bears N.87°W., 195 lks. mkd. ¼ S36 BT.

GL0 resurvey by Otto L. Draper, U.S. Transitman - Under instructions dated March 12, 1921 - (DCSO rec Vol 22 Pg 9238)

-----  
Intersect the ¼ sec. cor. established for secs. 1 and 36 which is a squared Fir stake, 3x3x18 ins. above ground, badly decayed, no marks legible.

This cor. will hereafter refer to sec. 36 only, destroy scribe marks on old SW BT. In place of old cor. stake:

Set an iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 36 only, with brass cap mkd.

¼ S 36  
1928

from which

A Fir snag, 14" dia., bears N.86°E., 158 lks. (not S.86°E., 162 lks.) mkd. ¼ S36 BT (not ¼ S1 BT) old BT).

A Fir 30" dia., bears S.87°W., 159 lks. (not N.87°W., 195 lks.) mkd. ¼ S1 BT (not ¼ S36 BT) old bearing tree.

A Fir 18" dia., bears N.26°E., 52 lks. mkd. ¼ S36 BT.

A Fir 10" dia., bears N.63°W., 81 lks. mkd. ¼ S36 BT.

Milo E. Godfrey, Deputy - Vernon Tracy - Mike Stone - Aug. 1962 - C.S. File 52/30-11

-----  
Found - Brass cap set by GL0 in 1928 at cor.  
18" Fir N.26°E., 34.3 ft. good scar.  
10" Fir N.63°W., 53.5 ft. good scar.  
30" Fir N.82°W., (Not S.87°W.) 104.9 ft. -  
previously cut open & scribing visible.  
14" Fir snag, N.86°E., 104.3 ft. old axe mks visible

Fd. ok by V. R. Tracy, 10/1966 C.S. File 52/30-28A

John Ransom, USFS - Jonathan Drew - 10/2010 - C.S. File 65/72-13

-----  
Found - Standard GL0 3" Brass Cap on 1" Iron Pipe projecting 11" above ground. Cap marked: "¼ S36 1928"  
30" Fir Snag N.82°W., 104.9 ft 6' tall snag tag reads N.83°W. 105.3 ft  
10" Fir Stump N.63°W., 53.5 ft., healed face.  
18" Fir Stump N.26°E., 34.3 ft., healed face. cont.

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

New - Painted 6" Band around BTs and face scars, attached new nails to signs. Cleared Brush around corner. marked new trees:  
 8" Fir BRS N.15°30'W., 30.0 ft scribed "¼ S36" "BT" on double blaze  
 8" Fir BRS N.54°30'E., 27.2 ft scribed "¼ S36" "BT" on double blaze  
 16" Fir BRS S.71°E., 48.5 ft scribed "X" "BT" on double blaze

Note - Corner falls just south of recently rebuilt PVT road bears E-W, take Scardman Creek Road to 018 spur brs East, follow east bound road to where fence on south side begins, just West of where fence starts is more open timber and posted line visible from road, corner falls in this open timber no more than 100 ft from road.

REMARKS- Line Maintained .5 mile East  
 Line Maintained .5 mile West  
 New BTs measured with staff compass(15°45' DEC) and tape.  
 New BTs include 3/4" brass washer nailed to face between B & T on lower blaze.

PLANE COORDINATE POSITION DATA  
 State OR Zone UTM-10M  
 North 4799704  
 East 520181  
 Estab. By GCDB

---

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/17/2022 - C.S. File 67/54-15  
 -----

Found - 2½" brass cap on 1" iron pipe, proj 14"  
 Mostly burnt out 3 ft tall Fir stump N.83°W., 104.9'  
 Mostly burnt away 4"x8' Fir N.15°30'W., 30.0 ft., blaze gone.  
 Burnt-dead 17" D.Fir S.71°E., 48.0 ft (rec. 48.5 ft)  
 Fully healed double blaze, add 3½" PK nail, right side center.

New - Burnt-dead 16" D.Fir N.11°E., 19.0 ft. 3½" right side center, not blazed or scribed.  
 Burnt-dead 14" D.Fir N.46½°E., 26.7 ft. 3½" right side center, not blazed or scribed.  
 5/8"x30" I.Rod with DCS0 Yellow Plastic cap S.43°W., 21.6 ft, up 8"  
 5/8"x30" I.Rod with DCS0 Yellow Plastic cap N.53¼°W., 20.6 ft, up 8"

Note - Corner falls just south of E-W.  
 Continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Compass decl.  $14\frac{1}{2}^{\circ}\text{E}$ .  
See sketch in file  
Lat:  ~~$43^{\circ}04'13.16''\text{N}$~~  Long:  ~~$122^{\circ}15'44.81''\text{W}$~~   
 $43^{\circ}21'00.54''\text{N}$   $122^{\circ}45'03.65''\text{W}$