

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3508)  
-----  
Set a chinquapin post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S25 on N & S 36 on S faces from which  
    A Fir 28" dia., bears N.4 1/2°W., 23 lks., mkd 1/4 S25 BT.  
    A Dogwood, 4" dia., bears S.9 1/2°E., 20 lks., mkd 1/4 S36 BT.

Not found by DCSO, V.R. Tracy, 10/1966 - C.S. File 52/30-28A

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - June 6, 2012 - C.S. File 67/36-7  
-----  
Reported as not found.  
No monument found.  
No accessories found. After determining an approximate corner location using map info. & GPS we use stream to West (noted in orig. line calls) as guide for search area. We check all large fir stumps that relate well to stream but can find no evidence. No old chinquapins in area.  
Note - Forest was cut 50+ years ago. Many stumps are out of orig. position due to erosion.  
Compass decl. 15 1/2°E.

David Edwards - For: Seneca Jones Tbr Co. - Aug 2012 - M164-1  
-----  
Set - 5/8"x30" steel rebar with 2 1/2" dia., Alum. cap mkd: "LS 2339" and "2012" as per the 2009 BLM Manual. (See narrative for the procedure used in setting the corner.)  
    A 9" dia., fir scribed "1/4 S25 BT" bears N.81°E., 18.2'  
    An 8" dia., fir scribed "1/4 S36 BT" bears S.40°W., 11.8'  
    A 10" dia., fir scribed "1/4 S25 BT" bears N.50°W., 1.8'  
    A 6' steel post is set 2.0' N.85°E.  
Compass decl. 17°E.