

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; and 36, T24-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2783)

Set a basalt stone 16x10x6 ins., 12" in the ground, for ¼ sec. cor. mkd. ¼ on N. face, from which
A Fir 12" dia., bears S.70°E., 17 lks. dist. mkd. ¼ S BT.
A Fir 24' dia., bears N.75°W., 16 lks. dist. mkd. ¼ S BT.
Cor. is on a hillside sloping W. about 300 ft. above creek.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Nov. 14, 1966 - C.S. File 52/42 52/30-59

Found - Orig. 12" now 23" Fir S.70°E., 11.2 ft., opened and shows "BT" scribe. Alive.
Orig. 24" now 30" Fir N.75°W., 10.6 ft., shows good scar. Alive. Do not open.
No trace of stone called for at corner.

Set brass cap (in mound of stone) mkd.
County Surveyors Office
T24S R1W ¼ S 36
T25S S 1

1966

New BTs- 24" D.Fir S.20°W., 35.3 ft. mkd. ¼ S1 CS BT.
7" Laurel N.4°W., 19.3 ft. mkd. ¼ S36 CS BT.
Corner lies on S. side of small creek, course SW. on very steep westerly slope in area of several small bluffs.