

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3491)

Set a basalt stone 14x12x10 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 36" dia., bears N.80½°W., 43 lks. dist. mkd. ¼ S BT
An Alder 6" dia., bears N.52°E., 14 lks. dist. mkd. ¼ S BT
Cor. is on right bank of creek.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9109)

The ¼ sec. cor. established for secs. 31 and 36, which is a basalt stone, 6x12x12 ins. above ground, firmly set, marked ¼ on W. face, from which
A Fir 50" dia., bears N.80½°W., 43 lks. dist. mkd. ¼ S BT.
(Old BT)
The old BT in sec. 31 is dead and fallen.
I now change this cor. to refer to sec. 36 only, and Remark the stone ¼ S36 on W. face; from which
A Fir 8" dia., bears S.37°W., 46 lks. dist. mkd. ¼ S36 BT.
(New BT)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1966 - C.S. File 52/30-25

Found - Orig. 50" now stump, Fir, N.80½°W., 28.4 ft., shows "T" scribe.
8" Fir, now down, S.37°W., 30.4 ft., shows "¼ S36 BT" on unhealed blaze.
No trace of rock called for.
Set Brass cap at cor. mkd: County Surveyors Office
T 25 S
R 1 W ¼ S 36 | R1E
1966
Pipe set 14" in ground and build mound of stone 18" high.
New BTs- 8" W.Fir S.89°W., 12.9 ft. mkd. ¼ S36 CS BT.
24" Hemlock S.16°W., 18.6 ft. mkd. ¼ S36 CS BT.
Corner lies on right bank of Canton Creek.

Glenn Baughman - For: U.S. Forest Service - Sept. 1980 - C.S. file 58/229-39

Found - 1966 DCSO brass cap, properly mkd. on a 1" I.P, firmly set 15" above the ground.
(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 50" D.Fir stump, orig. BT, with scribe marks "4" visible, bears N.80½°W., 28.4 ft.
An 8" D.Fir snag, with scribe marks "¼ S36 CS BT" visible on an unhealed blaze, bears S.89°W., 12.9 ft.
A 24" Hemlock snag, with scribe marks "¼ S36 CS BT" visible on an unhealed blaze, bears S.18°W., 18.6 ft. (Rec. S.16°W.)
New BTs- 10" Cedar bears S.52°W., 33.8 ft. mkd. "¼ S36 BT" on a double blaze with a brass washer "LS 536" nailed into lower blaze.
16" D.Fir bears N.38°W., 61.3 ft. mkd. "¼ S36 BT" on a double blaze with a brass washer "LS 536" nailed into lower blaze.