

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700178

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only, T25-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Joseph A. Ganong and John G. Collins,  
Cadastral Surveyors, Under special instructions dated March  
12, 1921 - (DCSO records Vol. 21 Page(s) 9110)

-----  
Set an Iron post 3 ft. long, 2" dia., 28" in the ground for  
closing cor. of secs. 30 and 31, with brass cap marked

T25S	T25S	
R1W	S 30	CC
	S 31	
S36	R1E	
	1927	

from which

A Fir 12" dia., bears N.13°E., 27 lks. dist. mkd. T25S R1E  
S30 CC BT.

A Fir 10" dia., bears S.64°E., 63 lks. dist. mkd. T25S R1E  
S31 CC BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Oct. 1966 - C.S. File 52/30-26

-----  
Found - 1927 GLO brass cap appropriately marked.  
10" now 14" Fir, S.64°E., 41.6 ft. (face) previously  
opened, scribe marks visible. Alive.  
NE. BT, lying face down.

New BTs- 8" D.Fir S.37°E., 14.6 ft. mkd. CC S31 CS BT.

8" Pine N.44°E., 11.7 ft. mkd. CC S30 CS BT.

Cor. lies in logged off unit approx. 150 ft. N. of small  
ravine, course SW.