

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3489)

Set a basalt stone 16x14x12 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 10" dia., bears S.85°E., 45 lks. dist. mkd. ¼ S BT.
A Fir 36" dia., bears S.60°W., 31 lks. dist. mkd. ¼ S BT.
Cor. is on a steep hillside, sloping W.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9112)

The ¼ sec. cor. established for secs. 25 and 30, which is a basalt stone marked ¼ on W. face; from which
A Fir 14" dia., bears S.85°E., 45 lks. dist., old BT, the marks on which I now destroy.
A Fir 36" dia., bears S.60°W., 31 lks. dist., old BT, with marks grown over.
I now change this cor. to refer to sec. 25 only.
Alongside the stone, Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap mkd. ¼ S25 |
1927
from which
A Fir 6" dia., bears N.65°W., 52 lks. dist. mkd. ¼ S25 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1966 - C.S. File 52/30-33

Found - 1927 GLO brass cap, properly mkd., badly bent and nearly out of ground. We straighten and RESET. Orig. 36" now 40" Fir snag, S.60°W., 20.5 ft., very good scar. We do not open.
6" now 10" Fir, N.65°W., 34.3 ft., alive, shows good scar. Do not open.
Original basalt stone, showing "¼" chisel marks.
New BT - 9" D.Fir S.10½°W., 23.7 ft. mkd. ¼ S25 CS BT.
Cor. lies on moderate, changing to steep, W. slope and approx. 125 ft. N. of the ¼ cor. of sec. 30, T25S R1E.