

PRIMARY CORNER DESCRIPTION Sec Cor for 24 and 25 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3488)

-----

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 19, 30, 25 and 24, marked T25S S19 on NE.; R1E S30 on SE.; S25 on SW.; and R1W S24 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which

- A Fir 12" dia., bears N.8°E., 28 lks. dist. mkd. T25S R1E S19 BT.
- A Fir 12" dia., bears S.33°E., 52 lks. dist. mkd. T25S R1E S30 BT.
- A Fir 24" dia., bears S.18°W., 109 lks. dist. mkd. T25S R1W S25 BT.
- A Fir 48" dia., bears N.18°W., 36 lks. dist. mkd. T25S R1W S24 BT.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9113)

-----

The cor. established for secs. 19, 24, 25 and 30, which is a decayed post, with marks illegible; from which

- A Fir 16" dia., bears N.8°E., 28 lks. dist., old BT, the marks on which I now destroy.
- A Fir 18" dia., bears S.33°E., 52 lks. dist., old BT, the marks on which I now destroy.
- A Fir 28" dia., bears S.18°W., 109 lks. dist., old BT, with marks grown over.
- A Fir 48" dia., bears N.18°W., 36 lks. dist., old BT, with marks grown over.

I now change this cor. to refer to secs. 24 and 25 only, and in place of the decayed post,

Set an iron post, 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 24 and 25 only, with brass cap marked:

T25S	T25S
S24	R1E
S25	S 19
R1W	1927

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1966 - C.S. File 52/30-32

-----

Found - 1927 GLO brass cap, properly marked.  
 Orig. 28" now 36" W.Fir, S.14°W., 71.9 ft. (not S.18°W.) shows scribe marks on unhealed blaze, alive. (Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. 48" now 53" Fir, N.18°W., 23.8 ft., dead and shattered, scribe marks visible on face and reverse on overgrowth.  
New BTs- 8" W.Fir S.56°W., 11.2 ft. mkd. T25S R1W S25 CS BT.  
8" D.Fir N.12°W., 46.4 ft. mkd. T25S R1W S24 CS BT.  
Corner lies on southerly slope, approx. 360 ft. S. of top of spur and approx. 164 ft. N. of closing cor. of secs. 19 & 30, T25S R1E.