

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3487)

-----  
Set a basalt stone 12x12x10 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which  
A Madrona 16" dia., bears N.53°E., 12 lks. dist. mkd. ¼ S BT.  
A Madrona 10" dia., bears N.62°W., 15 lks. dist. mkd. ¼ S BT.  
Corner is on a hillside, sloping SW., about 150 ft. below sec. cor.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9114-15)

-----  
The ¼ sec. cor. established for secs. 19 and 24, which is a basalt stone, 12x12x8 ins., loosely set, mkd. ¼ on W. face, from which  
A Madrona 16" dia., bears N.53°E., 12 lks. dist., old BT, the mrks on which I now destroy.  
The old BT in sec. 24 is dead and fallen.  
I now change this cor. to refer to sec. 24 only.  
Alongside the stone, Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap marked  
¼ S24  
|  
1927  
from which  
A Madrona 8" dia., bears S.64°W., 7 lks. dist. mkd. ¼ S24 BT.  
A Fir 26" dia., bears N.45°W., 100 lks. dist. mkd. ¼ S24 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Nov. 1966 - C.S. File 52/30-45

-----  
Found - Basalt stone mkd. "¼W" on W. face, No trace of 1927 GLO brass cap.  
26" now 30" Fir stump, N.45°W., 66.0 ft. shows good scar, do not open.  
8" now 11" Madrone, N.64°W., 4.6 ft., previously opened and shows fragments of scribe. (Recorded as S.64°W.)  
Also found obliterated 16" madrone, N.53°E., 7.9 ft.  
(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set Brass cap at cor. mkd: County Surveyors Office  
T 25 S  
R1W ¼ S 24 | R1E  
1966  
New BTs- 6" Madrone N.39°E., 6.0 ft. mkd. ¼ S CS BT.  
5" Madrone N.21°W., 5.5 ft. mkd. ¼ S24 CS BT.  
11" Madrone N.64°W., 4.6 ft. remarked ¼ S24 CS BT.  
Corner lies at foot of 30 ft. bluff on top of 100 ft. high  
bluff.