

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3485-86)

Set a basalt stone 12x10x10 ins., 8" in the ground, for ¼ sec. cor, marked ¼ on W. face, from which
A Fir 24" dia., bears S.17°E., 19 lks. dist. mkd. ¼ S BT
A Fir 48" dia., bears S.27°W., 31 lks. dist. mkd. ¼ S BT
This cor. is on a steep hillside, sloping SW.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9117)

The ¼ sec. cor., established for secs. 13 and 18, which is a basalt stone, 6x10x10 ins., above ground, firmly set, marked ¼ on W. face. I now change this cor. to refer to sec. 13 only. Re-Mark the stone ¼ S13 on W. face; from which
A Fir 30" dia., bears S.17°E., 19 lks. dist., old BT, the marks on which I now destroy.
A Fir 48" dia., bears S.27°W., 31 lks. dist., old BT, with marks grown over.
A Cedar 12" dia., bears N.42°W., 18 lks. dist., mkd. ¼ S13 BT. (New BT)

G. Robert Lecklider - For: U.S. Plywood Corp. - Aug. 1960 - M 19-46

Found - 48" Fir S.27°W., 20.5 ft.
12" Cedar N.42°W., 56.2 ft.
Set steel tube with survey cap.

Searched for, not fd, DCSO, Nov. 1966 - C.S. File 52/30-44A

William Ruppert - For: U.S. Forest Service - Nov. 1978 - C.S. File 58/176-12A

Found - 5/8" steel tube buried 12" under the bern at the side of a skid trail. 1" alum. cap attached marked "Property Corner".
36" D.Fir stump with axe marks in bark bears S.26°55'W., 20.8 ft.
12" Cedar stump cut approx. 36" high with face charred from slash fire bears N.44°05'W., 55.8 ft.
Replaced tube with 2" x 30" galv. steel pipe 26" in the ground. Plant tube next to pipe. Marked the attached 2½" brass cap "T25S R1W ¼ S13 PLS 866 1978." (Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 15" Cedar "¼ S13 BT" and attached brass washer mkd. "L.S. 866" bears S.20°55'W., 77.8 ft.
Drove green 6 ft. steel fence post 18" into the ground and painted red, bears N.45°56'W., 55.8 ft. Constructed mound of stones around the 2" x 30" steel pipe.

Gerald V. Nygren - For: U.S. Forest Service - June 11, 1987
-C.S. File 63/50-9

Found - 1978 Brass cap set by PLS 866, properly marked.
36" Fir stump, bears S.26°55'W., 20.8 ft.
12" Cedar stump, bears N.44°05'W., 55.8 ft.
16" Cedar bears S.20°55'W., 77.8 ft.
A 6 ft. steel fence post, bears N.45°56'W., 55.8 ft.
New BT - 8" D.Fir bears N.37°W., 7.0 ft. with single blaze scribed "¼ S13 RS1035 BT". A ½" brass washer marked "RLS 1035" is nailed flush to lower end of blaze.

"I hereby certify the above corner point was perpetuated as hereon described on June 11, 1987. U.S.F.S. bearing tree signs and monument signs were place on all BTs without them and a 6" red band was painted around each BT."