

PRIMARY CORNER DESCRIPTION Wit Cor. (South) to Secs. 12 & 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3485)

Set a basalt stone 14x12x6 ins., 10" in the ground for witness cor. of secs. 7, 12, 13 and 18, marked W C on NE. face, with 2 notches on N. and 4 notches on S. edges, from which

A Fir 16" dia., bears N.58°E., 20 lks. dist. mkd. WC T25S R1E S7 BT.

A Fir 36" dia., bears N.89°W., 20 lks. dist. mkd. WC T25S R1W S12 BT.

Cor. is on a steep hillside sloping W.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9117-18)

The witness cor. on the S. side of bluffs, established for secs. 7, 12, 13 and 18, which is a basalt stone, 6x12x6 ins. above ground, firmly set, mkd. WC on NE. face, with 2 notches on N., and 4 notches on S. edges. I now change this cor. to refer to secs. 12 and 13 only. Re-Mark the stone WC S12 on NW., and S13 on SW. face; from which

A Fir 20" dia., bears N.58°E., 20 lks. dist., old BT, the marks on which I now destroy.

A Fir 30" dia., bears S.24°W., 48 lks. dist. mkd. WC T25S R1W S13 BT (New BT)

A Fir 40" dia., bears N.89°W., 20 lks. dist., old BT, with marks grown over.

(The point for the cor. of secs. 12 and 13 only falls on the face of bluffs.)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1966 - C.S. File 52/30-43

Found - Rock marked "WC S12" on NE. and "S13" on SW., firmly set 1.3 ft. N. of C.C. of secs. 7 & 18, T25S R1E which is a 1927 GLO brass cap.

Orig. 40" now 40" Fir snag, N.89°W., 13.2 ft. (slope) shows good scar, we do not open.

30" now 34" Fir S.24°W., 31.7 ft., now stump, shows good scar.

Orig. 20" now 20" Fir snag, N.58°E., 13.2 ft. (recorded as being obliterated, frag. scribe marks visible on chopped face.)

(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700479

PRIMARY CORNER DESCRIPTION Wit Cor. (South) to Secs. 12 & 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 12" Cedar S.71°W., 40.3 ft. mkd. W.C. T25S R1W S13
CS BT.
12" Pine N.14°W., 106.3 ft. mkd. W.C. T25S R1W S12
CS BT.
This cor. lies on precipitous W. slope on N-S cutting line,
cut off to W.

William Ruppert, LS 866 - For: U.S. Forest Service - Nov.
1978 - C.S. File 58/176-12C

Found - 39" D.Fir N.87°06'W., 13.2 ft. with good scar.
33" D.Fir stump S.25°04'W., 31.7 ft. scribing
partially visible.
11" Cedar bears S.73°12'W., 39.9 ft. with good
scar.
12" Pine, N.14°08'W., 107.9 with good scar.
Set a 2" x 30" galv. steel pipe 24" into the ground and
constructed a mound of stones around it. Brass cap marked
"T25S WC S12 S13 R1W R1E PLS 866 1978."