

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 12 only, (East)


Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 8 Page(s) 3482-83)

 Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for cor. of secs. 6, 7, 12 and 1, marked T25S S6 on NE.; R1E S7 on SE.; S12 on SW.; and R1W S1 on NW., faces with 1 notch on N. and 5 notches on S. edges, from which
 A Fir 16" dia., bears N.26°E., 49 lks. dist. mkd. T25S R1E S6 BT.
 A Fir 48" dia., bears S.54°E., 30 lks. dist. mkd. T25S R1E S7 BT.
 A Fir 60" dia., bears S.48°W., 29 lks. dist. mkd. T25S R1W S12 BT.
 A Fir 24" dia., bears N.71°W., 4 lks. dist. mkd. T25S R1W S1 BT.
 Cor. is on the summit of a mountain, 350 ft. above creek noted at 57.50 chs. on this line bet. secs. 1 and 6.

GLO Resurvey by Joseph A. Ganong and John G. Collins, Cadastral Surveyors, Under special instructions dated March 12, 1921 - (DCSO records Vol. 21 Page(s) 9120-21)

 The cor. established for secs. 1, 6, 7 and 12, which is a badly decayed Fir post, with marks illegible. I now change this cor. to refer to secs. 1 and 12 only. In place of decayed post
 Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 1 and 12 only, with brass cap marked:



from which
 A Fir 20" dia., bears N.26°E., 49 lks. dist., old BT, the marks on which I now destroy.
 A Fir 48" dia., bears S.54°E., 30 lks. dist., old BT, the marks on which I now destroy.
 A Fir 60" dia., bears S.48°W., 29 lks. dist., old BT, with marks grown over.
 A Fir 30" dia., bears N.71°W., 4 lks. dist., old BT, with marks grown over.
 Cor. is on a spur, sloping W.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 1 & 12 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Nov. 1966 - C.S. File 52/30-51

Found - 1927 GLO brass cap, properly mkd. and nearly out of
ground. RESET brass cap 12" in ground and build
mound of stone 15" high around.
Orig. 60" now 60" Fir stump, cut low, S.48°W., 19.1
ft., no scribe.
Orig. 30" now 31" Fir, N.71°W., 26.4 ft. (recorded
4 lks., should be 40 lks.) Scribe marks visible
on nearly healed blaze. Alive.
Obliterated BTs to NE. and SE., now turned out.
New BTs- 11" W.Fir S.74°W., 61.6 ft. mkd. T25S R1W S12 CS BT
5" Hemlock N.59°W., 29.4 ft. mkd. S1 CS BT.
Cor. lies at NE. cor. of cut off unit on top of round spur.

Survey by Kristian DeGroot, LS #1941 - For: U.S. Forest
Service - April/May 1992 - C.S. File 63/138-20(F)

Found - 2" GLO 1927 Iron pipe, firmly set, projecting 9"
above a 30" dia. mound of stone, with a 2½"
properly mkd. brass cap.
60" D.Fir stump bears S.48°W., 19.1 ft. with a
healed blaze. (1896)
32" D.Fir stump bears N.71°W., 26.4 ft. with a
healed blaze and a sheet metal cap over the
stump. (1896 BT)
6" W.Fir bears N.59°W., 29.4 ft. with scribe marks
visible. (Rec. Hemlock) 1966 BT.
14" W.Fir snag bears S.74°W., 61.6 ft. with scribe
marks visible. 1966 BT.
New BT - 10" W.Fir bears S.23°W., 73.0 ft. scribed T25S R1W
S12 BT.

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-49

Found - 1927 GLO 2½" brass cap on iron pipe
BTs- 36" Fir stump, N.71°W., 26.2 ft "steel plate on top"
12" D.Fir, N.59°W., 29.4 ft. "healed face"
60" D.Fir stump, S.48°W., 19.1 ft
New BT - (BLAZED FACE ONLY),
11" D.Fir, S.5°E., 19.3 ft.
Note - From the map M177-49 the West closing corner secs.
6 & 7 bears S.3°08'18"E., 152.12' (DCSO JC)