

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 700637

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T25-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Resurvey by Joseph A. Ganong and John G. Collins,
Cadastral Surveyors, Under special instructions dated March
12, 1921 - (DCSO records Vol. 21 Page(s) 9121-22)

Set an Iron post 3 ft. long, 1" dia., 28" in the ground for
1/4 sec. cor. of sec. 6 only, with brass cap mkd. | 1/4 S 6
1927

from which

- A Fir 16" dia., bears N.29°E., 30 lks. dist. mkd. 1/4 S6 BT
- A Fir 24" dia., bears S.42°E., 36 lks. dist. mkd. 1/4 S6 BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct/Nov. 1966 - C.S. File 52/30-49

Found - 1927 GLO brass cap, set in mound of stone and
properly marked.

16" now 18" Fir, N.29°E., 19.8 ft., previously
opened and scribe visible. Alive. Rescribed
above old blaze, "1/4 S6 CS BT"

24" now 28" Fir S.42°E., 23.8 ft., shows good scar,
do not open. This BT is directly behind a 36"
D.Fir from Brass cap.

New BT - 18" D.Fir S.9°E., 12.0 ft. mkd. 1/4 S6 CS BT.

Corner lies approx. 125 ft. S. of new logging road and 180
ft. S. of 1/4 cor. Sec. 1, T25S R1W.