

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION W C Secs. 7 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9339)

-----  
N.0°04'W bet. Secs. 7 & 8, at 37.20 chains

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for witness cor. to ¼ cor. of secs. 7 & 8, with brass cap mkd

¼  
S 7 | S 8  
W C  
1928

from which

- A fir, 6" dia., bears N.44°E., 25 lks., mkd: W C ¼ S8 BT.
- A fir, 6" dia., bears N.60°W., 5 lks., mkd: W C ¼ S7 BT.

At 40.00 chains: Point for the ¼ sec. cor. falls in creek, impracticable to set cor.