

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9313)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for
1/4 cor. of secs. 28 & 29, with brass cap mkd

1/4
S 29 | S 28
1928

from which

A fir, 20" dia., bears N.65°E., 62 lks., mkd: 1/4 S28 BT.

A fir, 8" dia., bears N.85°W., 64 lks., mkd: 1/4 S29 BT.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flauser;
Nov. 6, 1996 - C.S. File 65/9-33

Found - 2 1/2" dia. brass cap on 1" O.D. iron pipe, protrudes
14" above ground. (U.S. General Land Office
Survey, 1928; Original corner)
20" now 24" dia. D.Fir with a fully healed single
blaze, bears N.65°E. 40.9 ft (agrees w/rec.) OBT
8" now 9" D.Fir with a fully healed single blaze,
bears N.85°W., 42.2 ft. to center of trunk 42.9
ft. to center of root crown. (rec. N.85°W., 42.2
ft.) OBT

New - 11" dia. W.Fir double blazed and scribed "1/4 S29 CS
BT" bears S.33°W., 16.0 ft.

21" dia. Maple double blazed and scribed "1/4 S28 CS
BT" bears N.79°E., 35.0 ft.