

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9316)

Set an iron post, 3 ft. long, 2" dia., 25" in the ground, for cor. of secs. 16, 17, 20, & 21, with brass cap mkd

T25S | R2E
S17 | S16
S20 | S21
1928

from which

- A fir, 10" dia., bears N.52°E., 15 lks., mkd: T25S R2E S16 BT.
- A fir, 16" dia., bears S.41°E., 23 lks., mkd: T25S R2E S21 BT.
- A chinquapin, 5" dia., bears S.42°W., 48 lks., mkd: T25S R2E S20 BT.
- A fir, 10" dia., bears N.16°W., 54 lks., mkd: T25S R2E S17 BT.

James N. Landrum, U.S.F.S. & Deputy, Doug. Co. Surveyors Office - Wit: Leonard Herzstein - May 10, 1983 - C.S. 62/10-19

Found - 2" dia. iron post, firmly at, projecting 12" above ground, leaning slightly northerly, with 1928 GLO brass cap marked: "T25S R2E S17 S16 S20 S21 1928". Used point where the I.P. comes out of the ground as the corner point.

12" D.Fir stump, N.52°E., 9.3 ft. with log alongside with scribe marks "5S 2E S6 BT" visible on partially healed blaze.

12" D.Fir, N.16°W., 35.6 ft. with healed blaze.

Set - Added a 2 ft dia. mound of stone. Iron pipe now projecting 4".

New BTs- 6" D.Fir, S.41½°E., 12.8 ft. scribed "T25S R2E S21 CS BT" on a single blaze.

6" D.Fir, S.25½°W., 30.2 ft. scribed "T25S R2E S20 CS BT" on a single blaze.

Note - Corner is in cutting line of old clearcut unit on steep east slope. To reach, proceed up USFS Rd. #3816 approx 2 miles from Steamboat Creek, then follow north boundary of clearcut unit #25-2E-16-1 approx. 1/4 mile to the corner. Corner is about 530 ft. west of 2 small cks.