

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9319)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T25S	R2E
<u>S 8</u>	<u>S 9</u>
S17	S16
1928	

from which

- A cedar, 16" dia., bears N.7°E., 36 lks., mkd: T25S R2E S9 BT.
- A cedar, 22" dia., bears S.76°E., 29 lks., mkd: T25S R2E S16 BT.
- A fir, 14" dia., bears S.75°W., 32 lks., mkd: T25S R2E S17 BT.
- A cedar, 5" dia., bears N.50°W., 56 lks., mkd: T25S R2E S8 BT.