

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9298)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 27, 28, 33, & 34, with brass cap mkd

T25S	R2E
S 28	S 27
S 33	S 34
1928	

from which

- A fir, 18" dia., bears N.16°E., 79 lks., mkd: T25S R2E S27  
BT.
- A fir, 6" dia., bears S.83°E., 43 lks., mkd: T25S R2E S34  
BT.
- A fir, 16" dia., bears S.29°W., 41 lks., mkd: T25S R2E S33  
BT.
- A fir, 14" dia., bears N.22°W., 53 lks., mkd: T25S R2E S28  
BT.