

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9303)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of secs. 15 & 22, with brass cap mkd

1/4 $\frac{S\ 15}{S\ 22}$
1928

from which

A hemlock, 20" dia., bears S.21°E., 7 lks., mkd: 1/4 S22 BT.

A hemlock, 22" dia., bears N.6°W., 100 lks., mkd: 1/4 S15 BT

Jim Landrum, USFS Deputy, Doug. Co. Surveyors Office - Leonard Herzstein - Oct. 31, 1983 - C.S. 62/10-4

Found - 1928 GLO brass cap on 1" diam. I.P. 36" long, lying on ground. Cap properly mkd.

24" Hemlock stump, S.44°W., 6.4 ft. (Rec. S.21°E. 4.6 ft.) with scribe marks "1/4 2 T" visible on partially healed blaze. (Blaze facing N.44°E. for a SW BT.)

30" Hemlock stump, N.6°W., 66.0 ft. with scribe marks "1/4 S BT" visible on partially healed blaze.

Set - Distance-distance from the center of the BTs would not intersect; and from the faces of the BTs would not match the blazed faces. At record bearing & distance from the orig. NW BT and from the direction of the face on the orig. SW (Rec. SE) BT, I RESET I.P. 30" in the ground in a 3 ft. mound of stone. I stamp "RESET 1983 CS" on brass cap.

New BTs- 5" hemlock, N.53°E., 13.0 ft. scribed "1/4 S15 CS BT" on single blaze.

12'x20'x8' high rock outcrop, S.42°W., 55.2 ft. marked "X BO" on highest point (along north edge).

Note - Corner is in USFS clearcut 25-2-15-1, approx. 130 ft. east and 200 ft. north of Reynolds Ck.