

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9289)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for
¼ cor. of secs. 22 & 23, with brass cap mkd

¼
S22|S23
1928

from which

A fir, 24" dia., bears S.66°E., 47 lks., mkd: ¼ S23 BT.

A fir, 14" dia., bears N.31°W., 12 lks., mkd: ¼ S22 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Travis Worthen - Sept. 12, 1977 - C.S. file 59/40-8

Found - 1928 U.S. GLO brass cap stamped U.S.G.L.O. ¼ S22 S23
1928. (Township & range not on Brass Cap) Pipe is
bent 90° & buried. Removed & straightened pipe,
then Re-Set in exact same location

Orig. 14" D.Fir bears N.31°W., 7.92 ft. is alive &
well. Has a healed blaze.

Orig. 24" now 31" D.Fir bears S.66°E., 31.02 ft. is
alive & well. Has a healed blaze. Placed County
BT signs on both.

Replaced Brass cap in exact orig. position.
No new accessories.

Note - Corner lies in a partial cut unit, 800 ft. SE of
Forest Service Road #2553.