

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9292)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd

T25S|R2E  
S10|S11  
S15|S14  
1928

from which

- A cross (X) on boulder, 12x10x10 ft. above ground, bears N.73°E., 16 lks., boulder marked X S 11 B O.
- A maple, 8" dia., bears S.20°E., 28 lks., mkd: T25S R2E S14 BT.
- A hemlock, 10" dia., bears S.64°W., 28 lks., mkd: T25S R2E S15 BT.
- A hemlock, 14" dia., bears N.57°W., 24 lks., mkd: T25S R2E S10 BT.