

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 2, 3, 10, & 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9294)

A cedar, 8" dia., for the cor. of secs 2, 3, 10, & 11; I mark
T 25 S S 2 on NE
R 2 E S 11 on SE
S 10 on SW and
S 3 on NW sides

from which

- A cedar, 12" dia., bears N.56°E., 24 lks., mkd: T25S R2E S2 BT.
- A hemlock, 10" dia., bears S.43°E., 51 lks., mkd: T25S R2E S11 BT.
- A cedar, 6" dia., bears S.44°W., 23 lks., mkd: T25S R2E S10 BT.
- A cedar, 20" dia., bears N.57°W., 44 lks., mkd: T25S R2E S3 BT.

Dennis Gaylord, USFS & deputy Douglas Co. Surveyor - Bill West - May 3, 1979 - C.S. File 60/24-29

Found - Orig. 8" now 10" corner tree is a cedar with single blazes on the NE, SE, SW, and NW faces. Scribing is visible in 3 of the blazes, which are nearly healed. The SE face is healed over completely.
Orig. 12" now 16" Cedar bears N.63°E., 16.3 ft. to center of tree and 15.84 ft. to face. Scribing visible in a single partially healed blaze.
Orig. 20" now 28" Cedar bears N.59°W., 30.5 ft. to center of tree at base and 29.04 ft. to face. Has a single healed blaze.
Orig. 6" now 10" Cedar bears S.46°W., 15.18 ft. scribing visible on a nearly healed single blaze.
Orig. 10" (?) now 31" Hemlock bears S.38°E., 35.7 ft. scribing visible on a partly healed single blaze "25 R2 11 T"

Set - I set a 1½" iron pipe with a 2½" brass cap attached. Brass capped monument is set alongside the corner tree north 0.5 ft. of the center of the tree. The brass cap is stamped:
"County Surveyors Office T25S R2E W.C. S3 S2 S10 S11 South 0.5 ft. 1979"

No new accessories.