

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION W C 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9288)

-----  
N.89°41'W., on true line bet. 23 & 26 at 34.27 chains  
Top of bluff, 40 ft. high, facing SW, set an iron post, 3 ft. long, 1" dia., 10" in the ground, to bed rock, and in mound of stone, 4 ft. base, for witness cor. to the ¼ sec. cor. of secs. 23 & 26, with brass cap marked

¼  $\frac{S23}{S26}$  WC  
1928

from which

A fir, 9" dia., bears North, 42 lks., mkd: WC ¼ S23 BT.

A fir, 18" dia., bears S.8°E., 49 lks., mkd: WC ¼ S26 BT.

At 39.86 chains

True point for ¼ sec. cor. falls on steep insecure ground, impracticable to set cor.