

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Witness cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9270)

N.0°01'W., between secs. 35 & 36 At 79.88 chs
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for witness cor. to the cor. of secs. 25, 26, 35, & 36, with brass cap mkd

W C	
T25S	R2E
<u>S26</u>	<u>S25</u>
S35	S36
1928	

from which

- A fir, 14" dia., bears N.45°E., 45 lks., mkd: WC T25S R2E S25 BT.
- A fir, 6" dia., bears S.43°E., 27 lks., mkd: WC T25S R2E S36 BT.
- A fir, 14" dia., bears S.56°W., 28 lks., mkd: WC T25S R2E S35 BT.
- A fir, 10" dia., bears N.48°W., 28 lks., mkd: WC T25S R2E S26 BT.

At 80.00 chains

Point for cor. of secs. 25, 26, 35, & 36, falls on face of low bluff, impracticable to set cor.