

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 11, 12, 13, & 14

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9278)

A fir, 14" dia., for the cor. of secs. 11, 12, 13, & 14; I mark

T 25 S S 12 on NE,
R2 E S 13 on SE,
S 14 on SW, and
S 11 on NW, faces

from which

- A fir, 26" dia., bears N.71°E., 40 lks., mkd: T25S R2E S12 BT.
- A fir, 14" dia., bears S.39°E., 27 lks., mkd: T25S R2E S13 BT.
- A fir, 16" dia., bears S.25°W., 40 lks., mkd: T25S R2E S14 BT.
- A fir, 20" dia., bears N.51°W., 16 lks., mkd: T25S R2E S11 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Bill West - May 3, 1979 - C.S. File 60/24-28

-
- Found -
- Orig. 14" Fir now a 15" D.Fir, corner tree has healed single blazes on the NE, SE, SW and NW sides.
 - Orig. 20" now 23" D. Fir bears N.49°W., 10.56, has a single healed blaze.
 - Orig. 16" now 17" White fir bears S.19°W., 26.4 ft. some scribing visible on a nearly healed single blaze.
 - Orig. 14" now 16" White fir bears S.46°E., 17.82 ft. Some scribing visible on a nearly healed single blaze.
 - Orig. 26" now 29" D.Fir bears N.75°30'E., 26.4 ft. has a single healed blaze.
- Set -
- I set a 1½" iron pipe alongside the corner tree. A 2½" brass cap, stamped "County Surveyors Office T25S R2E S11 S12 S14 S13 North 1.0 ft. W C 1979" is located 1.0 ft. south of the center of the corner tree.
 - No new accessories.