

TOWNSHIP 25 RANGE 02E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T25-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by John G. Collins, US Cadastral Engineer & Otto L. Draper, U.S. Transitman, under Special Instructions dated March 12, 1921, surveyed July 1928/Aug. 1930 - (DCSO records Vol. 22 Page(s) 9267-8)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd

T25S	
R2E	R3E
<u>S 1</u>	<u>S 6</u>
S12	S 7
1928	

from which

- A hemlock, 6" dia., bears N.70°E., 36 lks., mkd: T25S R3E S6 BT.
- A fir, 36" dia., bears S.65°E., 24 lks., mkd: T25S R3E S7 BT.
- A fir, 10" dia., bears S.42°W., 43 lks., mkd: T25S R2E S12 BT.
- A hemlock, 10" dia., bears N.60°W., 18 lks., mkd: T25S R2E S1 BT.