

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec Cor for Secs 30 & 31 (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original Survey by Hezekiah Johnson, Contract #721 dated May 1, 1900 (DCSO records, Volume 9 Page 3642)

-----  
At the point of intersection, I set a basalt stone 17x10x5 inches, 12" in the ground for closing corner of secs. 30 and 31 marked C C with 1 notch on S and 5 notches on N edges, from which

A Fir 15" dia., bears N.76°E., 81 lks., marked C C T 25 S R 2 W S 30 BT.

An Ash, 7" dia., bears S.19°E., 67 lks., marked C C T 25 S R 2 W S 31 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Pages 11510-11)

-----  
The original closing cor. of secs. 30 and 31, a basalt stone 16x10x4 ins., firmly set, mkd. with 5 grooves on N., 1 groove on S., and C C on E. face.

At point for corner, Set an iron post 3 ft. long, 2" dia., 28" in the ground, with the original basalt stone deposited at the base, for closing cor. of secs. 30 and 31, with brass cap mkd.

	T25S	
T25S	S30	CC
R3W	S31	
S36	R2W	

1943 from which

A Fir 30" dia. bears N.73°E., 55 lks., with blaze healed. (Old BT)

A Fir 16" dia. bear S.61°E., 103 lks., mkd. T 25 S R 2 W S 31 C C BT. (New BT)

Fd. Ok by D.Edwards, 4/1998 - M128-61

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23921)

-----  
The closing cor. of secs. 30 and 31, monumented with an iron post, 2" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd

from which the remains of an original bearing tree

A fir stump, 33" dia., bears N.73°E., 36.3 ft., with no marks visible on open, hollow blaze.

and a bearing tree mkd. by Price in 1943-44

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec Cor for Secs 30 & 31 (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 41" dia., bears S.61°E., 68.0 ft., with a healed blaze.  
and a new bearing tree  
A fir, 7" dia., bears N.48½°E., 27.6 ft., mkd. T25S R2W S30 CC BT  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.  
NAD 1983 (2011)  
Lat: 43°21'31.20 N Long: 122°59'24.72" W

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/22/2022 (Filed 4/14/2022) - C.S. File 67/52-21  
-----  
Found - 2½" GL0 brass cap (properly mkd) on 1½" ID iron pipe, projecting 3"  
26"x5 ft sawn, burnt fir stump N.73°E., 36.0 ft. to 3½" PK right side center (Rec 36.3 ft) face burned off. 1940  
42" burned Fir S.61°E., 66.7 ft. to 3½" PK nail RT side center (Rec. 68.0 ft.) 1940  
7" D.Fir N.48½°E., 27.8 ft. to PK nail RT side center (Rec. 27.6 ft) unhealed blaze scribes still visible.  
New - Burned 24" D.Fir S.81°E., 21.2 ft. not blazed, add 3½" PK nail, right side center.  
Burned 32" sugar pine S.31°E., 16.0 ft. to 3½" PK right side center, not blazed.  
Note - Corner is approx. 300' south of Rock Creek Rd.  
Corner is on flat ground in burnt over old second growth timber.  
Area burnt 9/2020  
Compass decl. 14½°E.  
LAT: 43°21'31.26" N LONG: 122°59'24.82" W