

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. ¼ Cor. for Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note: Original ¼ Corner common for Secs. 30, T25-2 and Sec. 25, T25-3 set by Laban Wheeler, Contract #467 dated April 7, 1883 (DCSO records, Volume 9 Page 3586)

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11511)

Mid-point of the W. bdy. of sec. 30. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 30 only, with brass cap mkd.

| ¼ 30
| 1943 from which

A Fir 24" dia. bears N.49°E., 133 lks., mkd. ¼ S 30 BT.
A Fir 30" dia. bears S.43°E., 159 lks., mkd. ¼ S 30 BT.

Doug. Co. Surveyors Office - Ray Tracy; Joe Brady; Jack Heritage - June 1966 - C.S. File 54/27-169

Found - 1943 GL0 brass cap mkd.
24" Fir, down and out of place, N.49°E., 87.8 ft., scribe visible on burned face.
30" now 57" Fir S.43°E., 104.9 ft., face burned, scribe barely visible, Rescribe "¼S CS". Tree is almost dead.

New BTs - 12" D.Fir N.44°E., 87.7 ft. mkd. ¼ S30 CS BT.
4" Pine S.12°E., 75.5 ft. mkd. "¼ S BT" (only)

This corner lies on NW edge of small clearing approx. 150x300 ft. on south slope.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/17/2022 (Filed 4/14/2022) - C.S. File 67/52-19

Found - 2½" GL0 brass cap (properly mkd) on ¾" ID IP projects 8".

Burnt 20"x7' Fir snag (rec 57" S.46°E., 101.3 ft. All marks gone (rec. S.43°E., 104.9 ft. 1940
Burnt 32" S.Pine S.13½°E., 73.3 ft. (Rec. S.12°E., 75.5 ft.) No visible marks. 1966

New - 12" burnt, dead, D.Fir N.50°E., 9.2 ft., 3½" P.K. nail RT side center.
18" burnt, dead, D.Fir S.48½°E., 14.3 ft., 3½" P.K. nail RT side center.
12" burnt, dead, D.Fir S.22°E., 13.0 ft., 3½" P.K. nail RT side center.

Note - Trees not blazed or scribed.

Area burnt 9/2020

Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

See sketch in file.
Lat: 43°21'57.51" N Long: 122°59'23.75" W