

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 24 only, T25-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3587)

-----  
Set Cedar post 3 ft. long, 3" sq., 24" in the ground for 1/4 corner marked 1/4 S on W face, from which

- A Maple, 10" dia., bears N.23°E., 17 lks. dist., marked 1/4 S BT
- A Cedar, 16" dia., bears S.46°E., 27 lks. dist., marked 1/4 S BT

-----  
GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11513)

-----  
Point for the original 1/4 sec. cor. which now refers to sec. 24 only, determined by reference to the record measurements from both old bearing trees. At point for corner, Set an iron post 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. of sec. 24 only, with brass cap marked:

1/4 S24 |

1943

from which

- A Red Cedar 22" dia., bears S.48 1/2°E., 27 lks. mkd. 1/4 S BT. I obliterate the marks on this old BT.
- A Maple, 11" dia., bears N.16°W., 17 lks., with old blaze healed. (Old BT)
- A Fir 50" dia., bears S.79 1/2°W., 41 lks., mkd. 1/4 S24 BT. (New BT)
- A Fir 36" dia., bears N.15 1/2°W., 49 lks., marked 1/4 S24 BT. (New BT).

-----  
Douglas County Surveyors Office - Randall Smith & Stephen Flause - 4/3/95 -C.S. 64/63 -2

-----  
Found - 2 1/2" GLO Brass cap on a 1" OD Iron pipe, protrudes 1' above ground.

10" now 13" dia, 25' high maple snag, with a fully healed single blaze, bears N.16°W., 12' (rec. N.16°W., 11.2' dist possible face measurement) new sprouts growing from base.

16" now 24" dia, 2' high cedar stump, no blazes or scribing visible, bears S.48 1/2°E., 17.8'.

50" now 50" dia, 2' high D.Fir stump, no blazes or scribing visible, bears S.79 1/2°W., 27.1'.

36" now 36" dia, 6' high D.Fir stump, with a fully healed single blaze, bears N.15 1/2°W., 32.3'.

New - 6" D.Fir, double blazed and scribed "1/4 S24 CS BT", bears N.73°W., 26.3'.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100347

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 24 only, T25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

4" Hemlock, double blazed and scribed "X BT", bears N.1½°W., 23.7'.  
12" Hemlock, double blazed and scribed "¼ S24 CS BT" on a single 5' high blaze, bears S.79°W., 11.6' (lower trunk is scared).

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749, surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23332-3)

-----  
The ¼ sec. cor. of sec. 24 only, T.25S., R.3W., perpetuated by the Douglas Co. Surveyor's Office in 1995, monumented with an iron post, 1" dia., firmly set, projecting 3" above the ground, with a brass cap (properly) mkd. from which the remains of bearing trees mkd. by Price in 1943-44

A D.Fir stump, 54" dia., bears S.79½°W., 27.1 ft., with no marks visible.

A decayed D.Fir stump, 38" dia., 5 ft. high, bears N.15½°W., 32.3 ft., with a healed blaze.

and BTs mkd. by the Douglas County Surveyor's Office

A hemlock, 20" dia., bears S.77¼°W., 12.0 ft., with scribe marks S CS visible on a partially healed blaze at breast height.

A D.Fir, 15" dia., bears N.74°W., 26.1 ft., with a healed blaze.

A hemlock, 9" dia., bears N.2¼°W., 23.4 ft., with a healed double blaze.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 1/27/2026 - C.S. File 67/62-07

-----  
Found - 2½" GL0 brass cap on 1" iron pipe proj. 15".  
Very rotted - burned 50" x 3 ft. fir stump S.79½°W. 27.1 ft. Add 3½" mag nail top center.  
Burned - solid 27" x 5 ft. D. Fir stump. N.15½°W. 32.3 ft. face burned off. Add 3½" mag nail right side center.  
Burned - sawn 22" x 2 ft. hemlock stump S.77¼°W. 12.0 ft. healed blaze. Add 3½" mag nail top center.  
Burnt - sawn 19" x ½ ft. fir stump N.74°W. 26.1 ft healed blaze. Add 3½" mag nail top center.  
Burned - sawn 12" x 1½ ft. hemlock stump North 23.4 ft. (Rec. N.2¼°W.) Healed blaze partly scribe visible. Add 3½" mag nail top center.

Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100347

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 24 only, T25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mon. Bent 1 ft. to west. Reference and reset mon. to plumb position projecting 15". Add large mound of stone.

Notes - Area burnt 9/2020  
Mon. on gentle East slope near East edge of square mile clearcut.

Compass decl. 14¼°E.  
TRIMBLE GEO XT LOCATION  
43.38166156° N. 122.98931837° W.