

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Hezekiah H. Johnson under Contract #721 dated May 1, 1900 (DCSO records, Volume 9 Pages 3648-49)

Intersect the W boundary of Tp. 6.52 chs. S of the cor. of secs. 13, 18, 19, and 24, which is a post 4" sq., marked and witnessed as described by the Surveyor general. At the point of intersection I set a fir post 3 ft. long 4" sq., 24" in the ground for closing cor. of secs. 18 and 19, marked C C T 25 S R 2 W on E., S 18 on N., and S 19 on S faces, with 3 grooves on N and S faces, from which

A Cedar 8" dia., bears N.21°E., 12 lks. dist., marked
C C T 25 S R 2 W S 18 BT.

A Fir, 60" dia., bears S.58°E., 31 lks. dist., marked
C C T 25 S R 2 W S 19 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11514)

The original closing cor. of secs. 18 and 19, the badly decayed remains of a fir stake, 3 ft. long, 4" square, on which no scribe marks remain. At point for corner, Set an iron post 3 ft. long, 2" dia., 28" in the ground, with decayed fir stake deposited at the base, for closing corner, with brass cap marked

	T25S	
T25S	S 18	CC
R3W	S 19	
S24	R2W	
	1943	

from which

A red cedar, 11" dia., bears N.66½°E., 28 lks. dist., with blaze healed. I reblaze and remark this old bearing tree T 25 S R 2 W S 18 C C B T.

A fir 64" dia., bears S.70°E., 54 lks. dist., with old blaze healed. (old BT)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy, Clete Putnam - June 6, 1962 -C.S. File 49/102-7

Found - Iron pipe with brass cap, 1943.
13" R.Cedar N.70°E., 18.6 ft. scribing visible on still open scar.
54" D.Fir S.70°E., 35.6 ft. shows good scars.
New BTs- 14" Hemlock S.28°E., 55.2 ft. mkd. T25S R2W CC S19 CS BT.
8" Hemlock S.82½°W., 20.8 ft. mkd. T25S R3W S24 CSBT

(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. Co. Surveyor Office - Vernon Tracy; Mike Stone; Jack Heritage - February 1966 - C.S. File 54/27-166

Found - 1943 GLO brass cap.
All BTs are now turned out or stumps including BTs recorded by Godfrey.
New BTs- 15" R.Cedar N.42°E., 49.1 ft. mkd: CC T25S R2W S18 CS BT.
9" Laurel S.21°E., 22.3 ft. mkd: CC T25S R2W S19 CS BT.
4" I.Pipe is driven into stump of 14" Hemlock S.28°E., 55.2 ft. Pipe is weld marked "T25S R2W S19 CC BT" and stands 4.4 ft. above stump.
Corner lies in NW corner of cut off unit.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Mar. 30, 1995 - C.S. 64/58-11

Found - 2½" dia GLO brass cap on a 2" O.D. iron pipe protruding 12" above ground. (1943 GLO)
5" now 12" dia., 25' high cedar snag with a partially healed rotted single blaze, scribing visible "T25S R2W S18" and a fully healed double blaze on south trunk, bears N.66½°E., 18.4' (agrees with 1943 rec,.)
60" now 64" dia. 2' high rotted D.Fir stump with evidence of a lower blaze, no scribing found, bears S.70°E., 35.6' (agrees with rec.)
New - 7" dia., hemlock double blazed and scribed "CCT25S R2WS18 CSBT" bears N.15½°E., 12.2 ft.
11" dia., Hemlock double blazed and scribed "CCT25S R2WS19 CSBT" bears S.58°E., 14.0 ft.
4" dia., hemlock double blazed and scribed "X BT" bears N.61°E., 4.0 ft.
8" dia., fir double blazed & scribed "CCT25S R2WS19 CSBT" bears S.12½°E., 18.1 ft.
Dec. 17¾°E

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23333)

The closing cor. of secs. 18 and 19, on the W. bdy. of the Tp., perpetuated by Godfrey, in 1962, further perpetuated by the Douglas Co. Surveyor's Office in 1966 & 1995, monumented with an iron post, 2" dia., firmly set, projecting 5" above the ground, with a brass cap (properly) mkd.
continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A red cedar snag, 11" dia., bears N.66½°E., 18.5 ft., with scribe marks T25S R2W S18 BT visible on a partially healed blaze. This snag is leaning to the SE.
A D.Fir stump, 54" dia., bears S.70°E., 35.6 ft., with no marks visible.
and BTs mkd. by the Douglas County Surveyor's Office in 1995
A hemlock, 10" dia., bears N.15°E., 12.0 ft., with a healed double blaze.
A hemlock, 6" dia., bears N.59¼°E., 4.0 ft., with a healed double blaze.
A hemlock, 15" dia., bears S.69¾°E., 14.0 ft., with a healed double blaze.
A D.Fir, 10" dia., bears S.14°E., 18.3 ft., with a healed double blaze.
The reference monument established by the Douglas County Surveyor's Office in 1966, an iron pipe, 4" dia., 8 ft. long, with weld marks T25S R2W S19 CC BT on the side of the pipe, was recovered lying on the ground, loose and out of position with no remains of the stump in which it was set; this position could not be determined or restored.
The geographic position in NAD 1983 (2011)
Latitude: 43°23'15.92"N. Longitude: 122°59'21.60"W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/21/2023 - C.S. File 67/56-39

Found - 2½" GLO 1943 brass cap (properly mkd) up 13". Leans slightly SSE
Burned, very rotted 48"x1½ ft. D.Fir stump S.70°E., 35.6 ft.
17"x1½ ft. hemlock stump S.68°E., 14.1 ft. (rec. S.69¾°E., 14.0 ft.) healed lower blaze, add 3½" mag nail top center.
Burned, sawn 12"x.75 ft. D.Fir stump S.12½°E., 18.3 ft. (rec. S.14°E.) portion of lower blaze add 3½" mag nail top center.
New - 5/8"x30" iron rod with DCS0 yellow plastic cap N.64°E., 13.0 ft. up 8".
5/8"x30" iron rod with DCS0 yellow plastic cap S.49½°E., 12.0 ft. up 8"
5/8"x30" iron rod with DCS0 yellow plastic cap N.9°W., 8.0 ft. up 10"
Note - Corner on shallow ESE slope in large burned clear cut approx. 200' S.45°E., from logging spur road
Area burnt 9/2020
Compass decl. 14½°E. Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only (West)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 202277.740 E 258484.987