

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 7 & 18 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11516)

Proportional Measurement. Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for closing corner of secs. 7 and 18, with brass cap mkd.

T25S
S7 CC
R3W S18
S13 R2W
1943

from which
An I.Cedar 20" dia., bears N.11 $\frac{3}{4}$ °E., 79 lks. mkd. T25S R2W S7 CC BT.
An I.Cedar 12" dia., bears S.63°E., 113 lks., mkd. T25S R2W S18 CC BT.

Douglas Co. Surveyors Office - Ray Tracy; Joe Brady, Jack Heritage - July/Aug. 1966 - C.S. File 54/27-181

Found - 1943 GL0 brass cap mkd.
20" now 24" I.Cedar N.11 $\frac{3}{4}$ °E., 52.1 ft. now stump, scribe visible on unhealed blaze.
12" now 21" I.Cedar S.63°E., 74.6 ft. alive, shows partial scribe marks on nearly healed blaze.
New BT - 18" I.Cedar N.84°E., 61.2 ft. mkd. T25S R2W S7 CSBT.

This cor. lies on very precipitous SW slope approx. 40 ft. N. of top of 80 ft. bluff, course NW and SE.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22788

The closing cor. of secs. 7 & 18, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 8 ins. above the ground, with brass cap (properly) mkd. from which bearing trees mkd. by Price

A sawed, decayed cedar stump, size indeterminate, bears N.11 $\frac{3}{4}$ °E., 52.1 ft., with scribe marks 2W S7 CC BT visible on a weathered blaze.

A sawed, decayed cedar stump, 18" dia., bears S.63°E., 74.6 ft., with scribe marks 25 S R2W S18 CC BT visible on a partially healed blaze.

and a BT mkd. by the Douglas Co. Surveyor's Office, in 1966

A cedar, 26" dia., bears N.84 $\frac{3}{4}$ °E., 61.8 ft., with a healed blaze.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 7 & 18 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree
A fir, 11" dia., bears S.40¾°E., 37.8 ft., mkd. T25S R2W
S18 CC BT.

Fd as per rec. by R. Quimby, 2/2014 - M167-34 A&B

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff
Lorsung- 5/17/2023 - C.S. File 67/56-18

Condition report
Found - BLM brass cap (properly mkd)
Burnt-dead, 27" cedar N.84¾°W., 61.8 ft. blaze not
visible.
Burnt-dead 12" Fir S.40¾°E., 37.8 ft. fully healed
single blaze.
BTs re-tagged and flagged.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 207466.105
E 255342.091