

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100607

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Pages 3589-90)

Set Hemlock post 4 ft. long, 4" sq., 24" in the ground for corner to secs. 1, 6, 7 and 12, marked T25S S6 on NE., R2W S7 on SE., R3W S12 on SW. and S1 on NW faces with 1 notch on N and 5 notches on S edges, from which

- A Fir 24" dia., bears N.61°E., 57 lks. dist., marked T25S R2W S6 BT.
- A Fir 24" dia., bears S.69°E., 13 lks. dist., marked T25S R2W S7 BT.
- A Fir 36" dia., bears S.10°W., 19 lks. dist., marked T25S R3W S12 BT.
- A Fir 40" dia., bears N.21°W., 33 lks. dist., marked T25S R3W S1 BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11518)

Point for original corner which now refers to secs. 1 and 12 only, determined by reference to the record measurements from all of the original bearing trees. At point for corner, Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 1 and 12 with brass cap mkd.

| | |
|------|------|
| T25S | T25S |
| S1 | R2W |
| S12 | S6 |
| R3W | |
| | 1943 |

from which

- A Fir 36" diam., bears N.61½°E., 57 lks. dist., mkd. T25S R2W S6 BT., I obliterate the marks on this old bearing tree.
- A dead Fir 24" dia., bears S.59°E., 13 lks. dist., mkd. T25S R2W S7 BT. I obliterate the marks on this old bearing tree.
- A Fir 40" dia., bears S.9°W., 19 lks. dist., with blaze healed. (Old BT)
- A Fir 50" dia., bears N.24°W., 33 lks. dist., with blaze healed. (Old BT)

Douglas Co. Surveyors Office - Vernon Tracy; Jack Heritage August/Sept. 1966 - C.S. File 54/27-176 (C.S. 54/27-168 fd)

(Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 100607

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - GLO brass cap mkd. in 1943 with steel fence post set alongside.
All BTs destroyed by logging. No live trees available.
Mark stumps for new BTs:
40" Fir stump S.73°W., 41.2 ft. mkd. T25S R3W S12 CSBT.
43" Fir stump N.71°W., 46.0 ft. mkd. T25S R3W S1 CS BT.
This corner lies approx. 500 ft. North of closing corner of sections 6 & 7, T.25-2., in large logged off area.

David Edwards - For: Roseburg Resources Co. - July 2013 - M165-53

Found - Brass cap
New - 5" Fir scribed "T25S R3W S12 BT" bears S.67°W., 7.60'
12" Fir scribed "T25S R3W S1 BT" bears N.26°W., 12.75'
6 ft. steel post set 2 ft. north.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/14/2023 - C.S. File 67/57-29

Found - 2½" GLO brass cap (properly mkd) proj. 12"
Burned, rotted 36"x4 ft., Fir stump S.73°W., 41.2 ft. face gone.
Burned, sawn 6"x1 ft., fir stump blaze not visible S.67°W., 12.75 ft. (rec. 7.60 ft)
Singed, sawn 14"x1½ ft. Fir stump N.26°W., 7.5 ft (rec 12.75) scribes W S1 visible on partially healed single blaze, add 3" mag nail top center.
Note: distance to tree's reversed.
New - Burnt, sawn 15"x1 ft. D.Fir stump N.49°E., 14.1 ft. 3½" mag nail, top center.
Burnt, sawn 21"x1 ft. D.Fir stump S.71°E., 15.0 ft. 3½" mag nail, top center.
Burnt, sawn 9"x2 ft. D.Fir stump N.68½°W., 4.1 ft. 3½" mag nail top center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Mon. in large burnt clear cut moderate east slope ±170 ft. East of logging road.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 213184.782 E 255387.481