

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO recs Vol. 36 Page 15130)

Point for the center ¼ sec. cor. of sec. 31, at intersection with the E and W center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T25S R2W
C¼ S 31
1972

from which

- A hemlock, 7" dia., bears N.42°E., 48 lks., mkd. C¼ 531 BT
- A hemlock, 40" dia., bears S.54°W., 46 lks. mkd. C¼ S31 BT

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23924)

The center ¼ sec. cor. of sec. 31, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.

from which the bearing trees mkd. by Berry, Wofford, Popken, and Baughman in 1972-75

- A hemlock, 8" dia., bears N.42°E., 31.7 ft., with a healed double blaze.
- A hemlock, 47" dia., bears S.54°W., 30.4 ft., with scribe marks S31 BT visible on partially healed blaze.