

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3641)

Set a washed boulder 16x8x6", 11" in the ground for ¼ sec. cor. marked ¼ on N face, from which

A cottonwood, 6" dia. bears N.20°E., 30 lks. mkd: ¼ S30 BT

A fir, 12" dia., bears S.20°W., 62 lks., mkd: ¼ S31 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13237)

The sec. cor. of secs. 30 & 31, determined at record bearing & distance from the only remaining original bearing tree:

A W.Fir, 34" dia., bears S.20°W., 62 lks., with scribe marks BT visible on partly opened blaze.

At the corner joint

Set an iron post, 28" long, 2½" dia., 24" in the ground with brass cap marked:

¼ $\frac{S\ 30}{S\ 31}$

T25S R2W

1962

from which new bearing trees

A cottonwood, 16" dia. bears N.7½°W., 62 lks. mkd ¼ S30 BT

A hemlock 19" dia., bears S.32½°W., 77 lks., mkd ¼ S31 BT.

Fd. & used on BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15128-9)