

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3648)

Set basalt stone 16x8x6", 11" in the ground for ¼ sec. cor. marked ¼ on N face, from which
An arbutus, 9" dia., bears N.22°W., 29 lks., mkd: ¼ S18 BT
A fir, 7" dia., bears S.45°E., 13 lks., mkd: ¼ S19 BT.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13240)

The sec. cor. of secs. 18 & 19, monumented with a basalt stone, 16x8x6", firmly set 11" in the ground, marked ¼ on the N face, from which the original bearing trees:

A madrone, 15" dia., bears N.27°W., 30½ lks., with a healed blaze. (Rec bearing & dist, N.22°W., 29 lks.)
A broken hemlock, 20" dia., bears S.40°E., 13 lks., with a healed blaze. (Record bearing, S.45°E.)

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground & in a mound of stone, 2 ft. base, to top, with brass cap marked

¼ $\frac{S\ 18}{S\ 19}$

T25S R2W

1962

from which new BTs

A fir, 6" dia., bears N.2°E., 33½ lks., marked ¼ S18 BT.

A hemlock 15" dia., bears S.20°E., 35 lks., marked S19 BT.

Deposit the original corner stone alongside the iron post.

Kenneth Perkins, WEYCO - June 9, 1982 (Rec'd June 20, 1989) - C.S. File 62/63-8

Found - Stone & GL0 1962 brass cap.
OBT N.27°W., 30½ lks. Madrone down, out of place.
OBT S.40°E., 13 lks., Hemlock stub, no evidence of BT except bearing & dist.
1962 NE & SE BTs not found.

New - 24" I.Cedar, N.81½°E., 30.6 ft., "W" nail & plate.
6" Hemlock, S.18°W., 1.5 ft., "W" nail & plate.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - April 12, 1989 - C.S. File 62/63-8

Found - A 1962 BLM ¾" dia. brass cap on a 2½" dia. iron pipe leaning 9" southwest of plumb. BC/IP is found 8" below ground.
Measurements taken to plumb position of BC/IP CONT

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

7" fir now broken stump & roots of indeterminable size hemlock no scribing or blazes found, bears S.40°E., 8.6 ft. (agrees with 1962 BLM rec) OBT. (Northwest madrone gone, falls in cat road)
6" now 6" dia. 6" high rotted D.Fir stump with healed over axe marks found at bottom of lower blaze, no scribing, bears N.2°E. 22.1 ft (agrees with record) (1962 BLM BT)
15" now 18" dia. 1½ ft. high hemlock stump, no blazes or scribing fd, bears S.20°E. 23.1 ft. (agrees with rec.) (1962 BLM BT.)
35" dia. 4 ft. high cedar stump with "W" nail in west base. One W. Co yellow tag with a bearing & dist. of S.81½°W., 30.6 ft. We measure N.81½°E., 30.6 ft. (Not of record*)
9" hemlock with a silver & a yellow tag. Silver tag with a bearing and dist. of S.25°E., 1 ft; Yellow tag with a bearing and dist. of N.18°E., 1.5 ft. We measure S.13°W., 1.8 ft. (Not of record.*)
Set - 1962 BLM BC/IP is returned to plumb position, now protrudes 2" above ground.
New BTs- A multi trunked madrone double blazed and scribed "X BT" on 4" south trunk, bears N.2½°E., 17.5 ft. (to root crown)
12" hemlock double blazed & scribed "¼ S18 CS BT" bears N.89½°W., 25.7 ft.
9" hemlock double blazed & scribed "¼ S19 CS BT" bears S.13°W., 1.8 ft.
Corner lies on an E-W cut line at south edge of cat road.
Note - *1982 Weyerhaeuser notes rec'd 6/20/1989

Ron Quimby - For: Roseburg Resources - Feb 2014 - M167-34 A&B

Found - BLM brass cap (properly) mkd.
35" (4 ft tall) cedar stump bears N.81½°E., 30.6 ft.
9" Madrone N.2½°E., 17.5 ft visible scar
17" Hemlock bears N.89½°W., 25.7 ft visible scar
14" Hemlock bears S.13°W., 1.8 ft visible scar

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23344-45)

The ¼ sec. cor. of secs. 18 & 19, perpetuated by the Weyerhaeuser Timber Co. in 1989, further perpetuated by the Douglas Co Surveyor's Office in 1989, monumented with an iron post, 2½" dia., firmly set, flush with the ground, in a collar of stone, with a brass cap (properly) mkd. cont.

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by the Weyerhaeuser Timber Co.
An incense cedar stump, 34" dia., bears N.72½°E., 32.3 ft., with no marks visible and a "W" nail in face at the base of the stump.
A hemlock, 14" dia., bears S.4°W., 2.2 ft., with a healed blaze.
and BTs mkd. by the Douglas County Surveyor's Office
A hemlock, 16" dia., bears S.81½° W., 26.5 ft., with a healed double blaze.
The southerly-most trunk of a multi-trunk madrone snag, 7" dia., bears N.5¾°W., 17.2 ft., with a healed upper blaze and scribe mark B visible on a partially healed lower blaze.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 2/18/2026 - C.S. File 67/62-15

Found - 3¼" BLM brass cap on 2½" I.P. proj 2" (properly mkd)
Sawn - burnt 22" x 3 ft. incense cedar stump. N.72°E. 32.3 ft. Add 3½" mag nail right side center.
Sawn - burnt 11" x 2 ft. hemlock stump S.14°W. 2.2 ft. (Rec. S.4°W.) Add 3½" mag nail right side center.
Sawn - burnt 22" x 2½ ft. cedar stump (Rec. Hemlock) S.81½°W. 22.0 ft. (Rec. 26.5 ft.) face visible inside. Add 3½" mag nail top center.
New - Burned - sawn 12" x 1½ ft. fir stump N.29°E. 10.7 ft. 3½" mag nail top center.
Notes - Area burnt 9/2020
Mon. on moderate west slope in very large newer clearcut. Mon. is approx. 125 ft. west of gravel road.
Compass decl. 14¾°E.
TRIMBLE GEO XT POSITION
43°.3789992 N. 122°.98279813 W.