

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3651)

Set basalt stone 16x8x8", 11" in the ground for ¼ sec. cor. marked ¼ on N face, from which
A hemlock, 8" dia., bears N.35°W., 47 lks., mkd: ¼ S7 BT.
A hemlock, 14" dia., bears S.16°W., 62 lks., mkd: ¼ S18 BT

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13241-2)

The ¼ sec. cor. of secs. 7 & 18, monumented with a basalt stone, 16x8x8", firmly set 11 ins, in the ground, marked ¼ on the N face, from which the only remaining original BT:
A hemlock, 28" dia., bears S.16°W., 62 lks., with fragmentary scribe marks visible on partly healed blaze
At the corner point
Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap marked
¼ $\frac{S}{S} \frac{7}{18}$
T25S R2W
1962
from which a new bearing tree
A hemlock, 15" dia., bears N.50°W., 78 lks., mkd: ¼ S7 BT.
Deposit the original corner stone alongside the iron post.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - 4/4/95 - C.S. 64/63-5

Found - 3¾" dia BLM Brass Cap on a 2½" OD Iron pipe is flush with top of a 2' dia. mound of stone.
One of the stones along north edge of Bc/Ip is firmly set vertically with evidence of marks on north face its top measures 6"x6". (orig. stone) we did not disturb to measure or check marks.
14" now 28" dia, 7' high rotting hemlock stump, shows evidence of axe marks and healed blaze, bears S.13°W., 40.9'.
15" now 16" dia., 6' high hemlock stump, with a fully healed single blaze, bears N.50°W., 50.1' (stump has a galvanized metal cap on top).
New - 19" dia., D.Fir double blazed and scribed "¼ S18 CS BT", bears S.44°E., 3.7'.
4" dia., D.Fir double blazed and scribed "x BT" bears N.29°E., 8' to root crown (pistol butt).
6" dia., Chinquapin, double blazed and scribed "¼ S18 CS BT", bears S.88°E., 9.9'.
_____ cont.

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCSO records Vol. 57 Page(s) 22796-7

The ¼ sec. cor. of secs. 7 & 18, perpetuated by the Douglas Co Surveyors Office in 1995, monumented with an iron post, 2½" dia., firmly set, flush with a mound of stone, 2 ft. base, 6" high, with brass cap (properly) mkd. from which the remains of an original bearing tree
A hemlock stump, 28" dia., bears S.12¼°W., 39.4 ft., with a healed blaze. (Record, S.16°W., 40.9 ft.)
and the remains of a bearing tree mkd. by Brooks
A sawed hemlock stump, 16" dia., bears N.50°W., 51.5 ft., with a healed blaze and a metal cover.
and BTs mkd. by the Douglas County Surveyor's Office
A fir, 5" dia., bears N.28¼°E., 8.2 ft., with a healed double blaze.
A chinquapin, 7" dia., bears S.89°E., 9.9 ft., with scribe marks ¼ S18 CS BT visible on a partially healed double blaze.
A fir, 22" dia., bears S.50°E., 3.4 ft., with a healed double blaze.

Fd as per rec. by R. Quimby, 2/2014 - M167-34 A&B

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 5/18/2023 - C.S. File 67/56-21

Found - 3¼" BLM brass cap (properly mkd) up 4"
Burned out snag 5" chinquapin S.89°E., 9.9 ft.
Burned, dead, 27" Fir S.50°E., 3.6 ft. (rec. 3.4 ft)
3½" mag nail right side center.
New - Burnt-dead, 15" chinquapin N.38°W., 22.7 ft. 3½" mag nail right side center.
5/8"x30" I.Rod N.1°W., 8.9 ft. with DCSO yellow plastic cap up 6"
5/8"x30" I.Rod S.68°W., 46.5 ft. with DCSO yellow plastic cap up 6"
Note - Area burnt 9/2020
Compass decl. 14½°E.
Monument on steep east slope, approx 85 ft north from dirt logging road.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 207706.312
E 257262.991