

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 148100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 9 Page(s) 3584)

-----  
Set Dogwood post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. corner marked 1/4 on N. face, from which  
A Chinquapin 4" dia., bears N.40°E., 29 lks. dist. mkd. 1/4 S BT.  
A Chinquapin 6" dia., bears S.20°E., 17 lks. dist. mkd. 1/4 S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO records Vol. 10 Page(s) 4276)

-----  
Searched for 1/4 sec. cor., but find no trace. Set temp. 1/4 sec. cor.  
Apportioned distance.  
Set a Cedar post, 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. of sec. 6, marked 1/4 S6 on S. face, from which  
A Fir 40" dia., bears S.31°E., 39 lks. dist. mkd. 1/4 S6 BT.  
A Fir 36" dia., bears S.54°W., 36 lks. dist. mkd. 1/4 S6 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 10, 1967 - C.S. File 54/40-54

-----  
Found - Remains of very old Cedar post, badly decayed, no scribing.  
40" now 60" Fir S.31°E., 25.7 ft., alive, shows good scar, do not open.  
36" now 56" Fir, S.54°W., 23.8 ft., alive, open and find "B" scribe.

Set Brass cap at cor. mkd: County Surveyors Office  
1/4 \_\_\_\_\_ T25S R2W  
S 6 T26S  
1967

New BTs- 7" D.Fir S.32°W., 14.3 ft. mkd. 1/4 S6 CS BT.  
14" D.Fir S.54°E., 15.2 ft. mkd. 1/4 S6 CS BT.  
Corner lies SW. slope.

BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15108)

-----  
The 1/4 sec. cor. of sec. 6 only, perpetuated and recorded by (Cont. Next Page)

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 148100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T26-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tracy in 1967, monumented with an iron post, 2" dia., firmly set, protruding 8" above ground, with brass cap mkd. as in 1967, from which bearing trees mkd. by Collier in 1913:

A Fir 60" dia., bears S.31°E., 39 lks. dist. with healed blaze.

A Fir 56" dia., bears S.54°W., 36 lks. dist. no marks visible on opened blaze.

and the remains of bearing trees mkd. by Tracy:

A Fir 14" dia., bears S.54°E., 23 lks. dist. with healed blaze.

A root hole bears S.32°W., 22 lks. dist., with a down Fir alongside, 12" dia., with scribe marks ¼ S6 CS BT visible on open blaze.

and a new bearing tree:

A Fir 8" dia., bears S.39°W., 78 lks. dist. mkd. ¼ S6 BT.

Fd. OK, March 1976 by G. Baughman - C.S. File 58/100-1

Frank O. Williams and Glen McChesney - For: Weyerhaeuser Co. April 28, 1976 - C.S. File 58/8-47

Found - 40" now 56" orig. Fir, bears S.32°E., (Rec. S.31°E.) 25.7 ft. to center of tree. Old healed face.

36" now 44" Fir, bears S.54°W., 23.8 ft. to center of tree, lower face had been opened, now pitched over.

1967 DCS0 brass cap.

7" now 8" Fir, down, bears S.32°W., 14.3 ft. to root hole, scribing and tag visible.

14" now 16" D.Fir bears S.54°E., 15.2 ft. to center of tree, scribing and tag visible.

Accessories added this date:

56" Fir bears S.33°E., 22.7 ft. (orig. 1914 BT) with "W" nail and plate.

44" Fir bears S.54°W., 21.8 ft. (orig. 1914 BT) with "W" nail and plate.

Kevin Schinnell - For: Rosboro Lumber Co. - 1/2006 - M 149-35

Found - 2½" brass monument on 2" iron pipe, 1.0' visible (leans to the SW) and accessories as follows:

48" fir stump S.32°E., 22.96'

48" fir stump S.57°W., 21.80'

New - 29" fir N°34'E., 8.00'

Note - All accessories repainted and flagged at this time.

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23915-6)

-----  
The ¼ sec. cor. of sec. 6 only, perpetuated by Schinnell, in 2006; monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd. from which the remains of the BTs mkd. by Collier in 1913

A decayed fir stump, 48" dia., bears S.31°E., 25.7 ft. with a healed blaze

A decayed fir stump, 56" dia., bears S.54°W., 23.8 ft., no marks visible.

and the remains of a BT mkd. by the Douglas County Surveyor's Office in 1967, reported by Berry, Wofford, Popken, and Baughman in 1972-75

A decayed fir stump, 14" dia., bears S.54°E., 15.2 ft., no marks visible.

and a bearing tree mkd. by Schinnell

A fir, 33" dia., bears N.30°E., 9.0 ft., with axe marks visible on bark.

and new bearing trees

A fir, 8" dia., bears S.38½°E., 18.3 ft., mkd. X BT.

A fir, 12" dia., bears S.46°W., 23.1 ft., mkd. ¼ S6 BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/16/2023 - C.S. File 67/55-63

-----  
Found - 2½" brass cap (properly mkd) up 12"  
Burned, decayed, 48"x4 ft. Fir stump S.31°E., 25.7 ft. healed blaze add 3½" mag nail top center.

Burned, decayed, 56"x5 ft Fir stump S.54°W., 24.5 ft. (W-nail in face notch 21.8 ft)

Burned, dead 33" Fir N.30°E., 9.2 ft. (rec. 9.0 ft) add 3½" mag nail, right side center.

Burned, dead, 8" D.Fir S.37°E., 18.3 ft., partly healed lower blaze scribes illegible, add 3½" mag nail right side center.

Burned, dead, 12" D.Fir S.46°W., 24.6 ft. (rec. 23.1 ft) add 3½" mag nail right side center.

New - 16"x0.5 ft. burned, sawn, D.Fir stump, S.69°E., 37.0 ft., 3" mag nail top center.

Note - Area burnt 9/2020

Compass decl. 14½°E.

Continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 148100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T26-2

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Monument on moderate SW slope, old growth to north,  
very large clear-cut to South.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 186217.971 E 257663.107