

PRIMARY CORNER DESCRIPTION WC Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3646-7)

A point on edge of precipice 25 ft. high, drops E. Set temp. object & measure West 20 lks. onto safe ground & Set a basalt stone 16x110x8", 11" in the ground for cor. for cor. of secs. 17, 18, 19, & 20 marked W C with 3 notch on S & 5 notches on E edges, from which

- A fir, 36" dia., bears N.25°E., 8 lks., mkd: WC T25S R2W S17 BT.
- A fir, 36" dia., bears S.45°E., 19 lks., mkd: WC T25S R2W S20 BT.
- An arbutus, 10" dia., bears S.43°W., 38 lks., mkd: WC T25S R2W S19 BT.
- A hemlock, 5" dia., bears N.53°W., 38 lks., mkd: WC T25S R2W S18 BT.

Glen McChesney, WEYCO - 2/28/1959 - C.S. File 53/112-28

Found - Stone for WC is 13.2' W, mdk: WC. NW corner would be on rock bluff below WC.

BTs to NW, NE, SE good condition.
Dogwood BT to SW down, rotted.

- New - 38" Fir (OBT) N.16°E., 5 ft. added "W" nail & plate.
- 40" Fir (OBT) S.44°E. 11.6 ft added "W" nail & plate
- 12" Hem. S.30°W., 30.5 ft., "W" nail & plate.
- 8" Hem (OBT) N.52°W., 24.6 ft added "W" nail & plate

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13239)

The WC of the cor, ofsecs. 17 18, 19 & 20, monumented with a basalt stone, 16x10x8", loosely set 5" in the ground, marked WC on the E face, with 3 notches on the S & 5 notches on the E edge, from which the original bearing trees;

- A fir, 40" dia., bears N.25°E., 10 lks. with a healed blaze. (Record distance, 8 lks.)
- A fir, 40" dia., bears S.45°E., 21 lks., with a healed blaze. (Record distance, 19 lks.)
- A hemlock, 11" dia bears N.53°W. 38 lks. with healed blaze

At the corner point

Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap marked T25S R2W

WC
 S 18 | S 17
 S 19 | S 20

1962 continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 179400

PRIMARY CORNER DESCRIPTION WC Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree
A hemlock, 13" dia., bears S.28½°W., 47 lks., marked X BT.
Deposit the original corner stone alongside the iron post.

Fd. Ok by G. Baughman, 1/1976 - M56-35

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23344)

True point for the cor. of secs. 17, 18, 19, & 20, at record bearing and from the found original witness cor., and is located on a rock bluff where it is impracticable to establish a permanent monument, not monumented.
From the true point, the witness cor. for the cor. of secs. 17, 18, 19, & 20 bears W., 13.20 ft., monumented with an iron post, 2½" dia., firmly set, projecting 3" above the ground, in a collar of stone, with a brass cap (properly) mkd. from which the remains of the original bearing trees reported by Brooks in 1962
A D.Fir, 36" dia. on uphill side at breast height, bears N.25°E., 6.6 ft., with a healed blaze.
A D.Fir stump, 38" dia., bears S.45°E., 12.5 ft., with no marks visible. (Record, 13.9 ft.)
and a new bearing tree
A red cedar, 8" dia., bears S.54½°E., 10.4 ft., mkd. X in the bark at breast height and BT in low blaze.

2