

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezikiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3640-1)

-----

Set basalt stone 16x9x8", 11" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A pine, 40" dia., bears N.40°W., 10 lks., mkd: ¼ S31 BT.

A fir, 8" dia., bears S.60°E., 35 lks., mkd: ¼ S32 BT.

V.W. Hosford - For: Evans Products Co. - Feb./Oct. 1960 - C.S. File 51/144 - M19-77

-----

At this corner, I fd. the orig. marked stone, displaced by logging. At the true point of the corner, I drove a hub & placed the marked stone beside it. Both orig. BTs are living. The Fir is now 18" in dia. The Pine is now 50"

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13235-6)

-----

The ¼ sec. cor. of secs. 31 & 32, monumented with a basalt stone, 16x9x8", loosely set 6" in the ground, mkd on the W face, from which the original bearing trees:

A fir, 19" dia., bears S.60°E., 35 lks., with a healed blaze.

A W.Pine, 50" dia., bears N.40°W., 10 lks., with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" ins. dia., 16" in the ground to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap marked:

¼  
S 31 | S 32  
T25S | R2W  
1962

from which a new BT

A fir, 10" dia., bears N.88¼°E., 85 lks., mkd: ¼ S32 BT.

Deposit the orig. corner stone alongside the iron post.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford, & G. Steven Popken Cadastral Surveyors & Glenn S. Baughman, LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854, surveyed July 1972/Oct. 1975 - (DCSO recs Vol. 36 Page 15126)

-----

The ¼ sec. cor., of secs. 31 & 32, monumented with an iron post, 2½" dia., firmly set, in a mound of stone, 2½ ft. base, to top, with brass cap (properly) mkd.

from which the original bearing trees

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 24" dia., bears S.60°E., 35 lks., with a healed blaze.  
A W.Pine, 53" dia., bears N.40°W., 10 lks., with a healed blaze.  
and a bearing tree mkd. by Brooks, in 1962  
A fir, 13" dia., bears N.88¼°E., 85 lks., with healed blaze.

Fd. BC ok by R.Geisler, 8/9/1984, C.S. 58/146-4 - FD NE BT (Fir) to be SE.