

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3639)  
-----  
Summit of spur, slopes N. Set a basalt stone 16x8x6", 11" in the ground for cor. for cor. of secs. 29, 30, 31, & 32 marked with 1 notch on S & 5 notches on E edges, from which  
A chinquapin, 12" dia., bears N.36°E., 35 lks., mkd: T25S R2W S29 BT.  
A chinquapin, 9" dia., bears S.44°30'E., 32 lks., mkd: T25S R2W S32 BT.  
A chinquapin, 8" dia., bears S.13°W., 41 lks., mkd: T25S R2W S31 BT.  
A fir, 7" dia., bears N.12°30'W., 51 lks., mkd: T25S R2W S30 BT.

Glen McChesney, WEYCO - 8/20/1959 - C.S. File 53/112-45  
-----  
Found - Orig. stone with notches  
14" chinquapin, face rotted, N.37°E., 22.7 ft.  
12" chinquapin, scribing visible, face rotted, S.44°E., 21.6 ft.  
12" chinquapin, cat faces - not opened, S.13°W., 27.1 ft.  
22" fir, cat faces - not opened, N.11°W., 33.7 ft.  
ADDED "W" nail & plate.  
New - 18" Fir N.79°E., 13.0 ft., "W" nail & plate.  
9" Hemlock S.4°E., 35.5 ft., "W" nail & plate.  
22" Fir S.78°W., 37.5 ft., "W" nail & plate.

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13236)  
-----  
The cor. of secs. 29, 30, 31 & 32, monumented with a basalt stone, 16x8x6" firmly set 11" in the ground, marked with 1 notch on the S, & 5 notches on the E edge, from which the original bearing trees:  
A chinquapin, 17" dia., bears N.36°E., 36 lks., with no marks remaining on decayed blaze. (Rec dist 35 lks.)  
A chinquapin, 14" dia., bears S.44½°E., 33 lks., with fragmentary scribe marks visible on nearly healed blaze. (Record distance, 32 lks.)  
A chinquapin, 14" dia. bears S.13°W., 41. lks., with a healed blaze.  
A fir, 21" dia. bears N.12½°W. 51 lks. with a healed blaze  
At the corner point  
continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2½" dia., 22" in the ground with  
brass cap marked

T25S R2W  
S 30 | S 29  
S 31 | S 32  
1962

from which a new bearing tree

A fir, 20" dia. bears N.78°E., 21 lks. mkd T25S R2W S29 BT  
Deposit the original corner stone alongside the iron post.

BLM dependent resurvey by Daniel L. Berry, Harvey E. Wofford,  
& G. Steven Popken Cadastral Surveyors & Glenn S. Baughman,  
LS, under contract #52500-CT5-1116 & Group E 786, 848, & 854,  
surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s)  
15125-6)

-----  
The cor. of secs. 29, 30, 31, & 32, monumented with an iron  
post, 2½" dia., firmly set, protruding 6" above ground, with  
brass cap (properly) mkd.

from which the remains of the orig. BTs

A chinquapin snag, 18" dia., bears N.36°E., 36 lks., with  
no marks visible.

A chinquapin snag, 15" dia., bears S.44½°E., 33 lks., no  
marks visible.

A root hole bears S.13°W., 41. lks., with a down  
chinquapin alongside, 16" dia., with healed blaze.

A fir, 25" dia. bears N.12½°W. 51 lks. healed blaze  
and a BT mkd. by Brooks, in 1962

A fir, 24" dia., bears N.78°E., 21 lks. with healed blaze.  
and new BTs

A hemlock, 15" dia., bears S.3°E., 55 lks., mkd: T25S R2W  
S32 BT.

A fir, 15" dia. bears S.17°W. 94 lks. mkd: T25S R2W S31 BT

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor &  
Robert Browning, Surveying Technician, under Group #1659,  
surveyed June/July 1993 - (DCSO recs Vol. 51 Pages 19418-9)

-----  
The cor. of secs. 29, 30, 31, & 32, monumented with an iron  
post, 2½" dia., firmly set, projecting 2" above ground, with  
brass cap (properly) mkd.

from which the remains of the original bearing trees

A decayed chinquapin stump, size indeterminate, bears  
N.36°E., 36 lks., with decayed remains alongside, no  
marks visible.

A chinquapin snag, 15" dia., bears S.44½°E., 33 lks., with  
healed blaze.

A roothole, bears S.13°W., 41 lks., with a down chinquapin  
alongside, 16" dia., with healed blaze. cont next pg

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 30" dia., bears N.12½°W., 51 lks. with healed blaze and a bearing tree mkd. by Brooks  
A fir, 26" dia., bears N.78°E., 21 lks., with healed blaze and remains of BTs mkd by Wofford, Berry, Popken, & Baughman  
A sawed hemlock stump, 19" dia., bears S.3°E., 55 lks., with partially healed blaze.  
A fir, 18" dia., bears S.17°W., 94 lks., with healed blaze and a new bearing tree  
A hemlock, 4" dia., bears S.29½°E., 40 lks., mkd. X BT.  
The corner is located on a spur, sloping N.20°E.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 5/10/2022 (Filed 8/11/2022) - C.S. File 67/52-49  
-----  
Found - ¾" GL0 brass cap (properly mkd) on 2" I.D. iron pipe proj. 6" original corner stone on SW edge proj. 3"  
Orig. BT -Burnt-dead 32" Fir N.12½°W., 33.7 ft. with fully healed single blaze, add ¾" PK nail right side center.  
Brooks BT  
Burnt-dead 29" Fir N.78°E., 13.7 ft. with fully healed single blaze, add ¾" PK nail, right side center.  
Wofford BT  
Burnt-dead 26" Fir S.15¼°W., 62.0 ft. (rec. S.17°W.) with fully healed single blaze.  
New - Metal lath 1.0 east.  
Note - Area burnt 9/2020  
Corner is on a spur sloping N.20°E.  
Compass decl. 14½°E.  
See sketch in file.  
Lat: 43°21'29.85"N Long: 122°58'23.03"W