

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3646)

-----  
Set basalt stone 18x7x7", 12" in the ground for 1/4 sec. cor. marked 1/4 on W face, from which

A hemlock, 14" dia., bears S.75°E., 26 lks., mkd: 1/4 S20 BT

A hemlock, 18" dia., bears S.49°W., 40 lks., mkd: 1/4 S19 BT

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 -(DCSO records Vol. 32 Page(s) 13238-9)

-----  
The 1/4 sec. cor. of secs. 19 & 20, monumented with a basalt stone, 18x7x7", firmly set 11" in the ground, marked on the W face, from which the original bearing trees:

A hemlock, 22" dia., bears S.80°E., 27 lks., with scribe marks 1/4 S2 visible on opened blaze. (Record bearing & distance, S.75°E., 26 lks.)

A hemlock, 32" dia., bears S.49°W., 40 lks., with scribe marks 1/4 19 visible on partly healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground with brass cap marked

1/4  
S 19|S 20  
T25S R2W  
1962

from which new BTs

A hemlock, 9" dia., bears N.33 1/2°E., 72 1/2 lks. mkd: 1/4 S20 BT

A hemlock, 8" dia., bears S.83°W., 40 1/2 lks., mkd: 1/4 S19 BT

Deposit the orig. corner stone alongside the iron post.

Douglas Co. Surveyors Office - Vernon "Ray Tracy & Crew - Feb. 5, 1968 - C.S. File 54/27-124

-----  
Found - 1962 Cadastral Brass Cap & BT's. as follows:

Orig. 22" Hemlock, now snag, S.80°E. 17.8 ft., scribe visible on unhealed blaze, W" nail & tag.

Orig. 32" Hemlock, now stump, S.49°W. 26.4 ft., scribe visible, "W" nail & tag.

9", now 10" Hemlock, alive, N.33 1/2°E. 47.8 ft., scribe visible on unhealed blaze.

No trace of 1962 SW BT due to cat, road.

New BT - 7" Hemlock N.89°W. 42.2 ft. mkd. "1/4 S19 CS BT".

Note - This corner falls on N-S cutting line clear cut west Best route to 1/4 corner, follow cat, road from vicinity of section corner 1/2 mile south.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23343)

-----

The ¼ sec. cor. of secs. 19 and 20, perpetuated by the Douglas Co Surveyor's Office in 1968, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with a brass cap (properly) mkd.

from which the remaining bearing tree mkd. by Brooks in 1962

A hemlock, 15" dia., bears N.33½°E., 48.9 ft., with a healed blaze. (Record, 47.8 ft.)

and bearing tree mkd. by the Douglas County Surveyor's Office

A hemlock, 20" dia., bears S.88¾°W., 41.6 ft., with a healed blaze.