

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3649)  
-----  
Set basalt stone 18x8x6", 12" in the ground for 1/4 sec. cor. marked 1/4 on W face, from which  
    A fir, 40" dia., bears S.75°E., 3 lks., mkd: 1/4 S17 BT.  
    A cedar, 20" dia., bears N.65°W., 53 lks., mkd: 1/4 S18 BT.

Fd. ok by G. Baughman - 1/1976 M56-35

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 4/6/1989 - C.S. File 62/63-1  
-----  
Found - Original stone, firmly set measuring 6"x8" on top & protruding 7" above ground. Orig. stone is clearly marked "1/4" on west side. (When removed stone measured 18" long)  
    40" now 49" dia. D.Fir with a fully healed double blaze & axed marks on bark "L X" bears S.75°E., 4.5 ft. (Rec. S.75°E., 2.0 ft. possible face measurement) Orig. BT.  
    20" now 32" dia. 2 ft. high cedar stump, with a lower healed blaze; stump has a rotted out center with an axe mark at bottom of blaze. No scribing found. Bears N.71 1/2°W., 35.0 ft. (Orig. rec. N.65°W., 35.0 ft.) Orig. BT.

Set - Orig. stone is referenced and a 8 1/4" long boat spike with a 1 1/4" dia. head stamped "DCSO 1/4 1989" is set at reference position 15" below ground.  
    A 2 3/8" dia. brass cap on a 1 3/8" O.D. by 32" long I.P. is set over boat spike at referenced position and protrudes 13" above ground. Original stone is set along east edge of BC/IP with side mkd. "1/4" facing west, stone protrudes 4" above ground. BC/IP & orig. stone are surrounded by a 2 ft. dia. mound of stone.

New BTs- 4" D.Fir double blazed & scribed "X BT" bears S.44°W., 41.0 ft.  
    3" D.Fir double blazed & scribed "X BT" bears N.72 1/2°W., 23.6 ft.  
    A double trunked cedar double blazed & scribed on 11" dia. East trunk "1/4 S17 CS BT" bears North 24.2 ft.

Corner lies in a north-south cut line near the west edge of a small bench. Trees to the east are targeted for harvest in near future.

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - For: Roseburg Resources - Feb 2014 - M167-34 A&B  
-----

Found - DCS0 brass cap on iron pipe with stone alongside  
(properly) mkd.  
16" double trunked cedar. East trunk bears north  
24.2 ft visible scar  
11" D.Fir bears N.72°W., 23.6 ft visible scar  
12" D.Fir bears S.44°W., 41.0 ft visible scar.  
62" D.Fir bears S.75°E., 4.5 ft healed scar  
32" Cedar stump (2 ft tall) bears N.71°W., 35.0 ft.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and  
Jeff Lorsung - 2/3/2026 - C.S. File 67/62-06  
-----

Found - D.C.S.O. brass cap on iron pipe with stone along  
side in 2 ft. by 1 ft. stone mound.  
Burned - dead 20" double trunked cedar. East trunk  
North 23.8 (Rec. 24.2) good scar. Add 3½" mag  
nail right side center.  
12" x 1 ft. sawn - burned stump. N.71°W. 23.5 ft.  
(Rec. N.72°W. 23.6 ft.) Add 3½" mag nail top center.  
59" x 40 ft. D. Fir snag S.75°E. 4.7 ft. (Rec. 4.5 ft.) Add  
3½" mag nail right side center.  
New - 16" x 1 ft. sawn - burnt fir stump S.80°W. 39.0 ft.  
3½" mag nail top center.

Notes - Mon. Is in a North/South cut line on south sloped bench.  
Compass decl. 14¼°E.  
OCS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
N. 205025.174  
E. 259903.074