

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3650)

Set a basalt stone 16x9x9", 11" in the ground for cor. for cor. of secs. 7, 8, 17, & 18 marked with 4 notch on S & 5 notches on E edges, from which
 A hemlock, 26" dia., bears N.18°E., 27 lks., mkd: T25S R2W S8 BT.
 A hemlock, 10" dia., bears S.65°E., 20 lks., mkd: T25S R2W S17 BT.
 A fir, 40" dia. bears S.51°W. 79 lks. mkd: T25S R2W S18 BT
 A fir, 40" dia. bears N.64°W., 56 lks. mkd: T25S R2W S7 BT

V.W. Hosford - Oct. 1957 - C.S. File 42/308-1

After logging in sec 18, I found the original corner stone moved approximately two ft East from its orig position. I did not reset this stone. The orig BT for sec 8 is a dead snag . The orig BT for sec 17 is entirely gone. The orig BT for sec 18 is a stump with scribing visible. The orig BT for sec 7 in good condition.
At the true point of the corner, I drove a 1½" iron pipe 36" long, 24" in the ground, from which;
 A R.Cedar 44" dia. bears N.4°E., 56.0 ft. mkd S8 253 BT.
 A Fir 60" dia., bears S.54°E., 51.5 ft. mkd S17 253 BT.
 A Hemlock 22" dia. bears S.32½°W. 109.4 ft. mkd S18 253 BT
 A Fir 48" dia., bears N.64°W., 56 lks, orig BT.

Glen McChesney, WEYCO - 7/29/1959 - C.S. File 53/112-10

Found - 1½" IP set by Hosford.
 No trace of orig. stone.
 Orig. 38" Hemlock snag, scribing visible upper face, N.17°E., 17.8 ft. to face.
 Orig. SE BT gone.
 Orig. 48" Fir stump, scribing visible, bears S.52°W., 52.0 ft. to face. ADDED "W" nail & plate
 Orig. 48" Fir, faces not opened, bears N.65°W., 37.0 ft. ADDED "W" nail & plate
 1957 44" R. Cedar scribed S8 BT 253, bears N.3°E. ADDED "W" nail & plate.
 1957 46" Fir, scribed S17 BT 253, bears S.55°E., 51.4 ft. ADDED "W" nail & plate.
 1957 20" Hemlock scribed S18 BT 253, bears S.32°W., 109.0 ft.

continued next page

1

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 32 Page(s) 13240-1)

The cor. of sees. 7, 8, 17 and 18, perpetuated & recorded by Hosford in 1957, monumented with an iron pipe, 36" long, 1½" dia., 32" in the ground, from which the orig. BTs;

A hemlock snag, 40" dia., bears N.18°E., 29 lks., with scribe marks T25S R2W S8 visible on opened blaze. (Rec. dist. 27 lks.)

A sawed fir stump, 52" dia., bears S.51°W., 82 lks., with scribe marks W S18 BT visible on opened blaze. (Rec dist. 79 lks.)

A broken top fir, 52" dia., bears N.64°W., 60 lks., with a healed blaze. (Rec dist 56 lks.)

and trees marked by Hosford in 1957


A cedar, 50" dia., bears N.4°E., 89 lks. with scribe marks S8 253 BT visible on unhealed blaze.

A fir snag, 60" dia., bears S.54°E., 82 lks., with scribe marks S17 253 BT visible on unhealed blaze.

A sawed hemlock stump, 24" dia., bears S.32½° W., 166 lks, with no marks remaining.

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap marked



from which new bearing trees

A hemlock, 23" dia., bears N.28°E., 208 lks., marked T25S R2W BT S8.

A hemlock, 22" dia., bears S.76½°E., 172 lks., marked T25S R2W S17 BT.

No suitable bearing trees available in secs. 7 and 18.

Deposit the iron pipe alongside the iron post.

The cor. falls in spring seepage, drain South.

Fd. Ok by G. Baughman, 1/1976 - M56-35

Harvey Christensen - 1/1999 - C.S. File 65/23-12

Found - 3¾" BLM brass cap on 2½" IP, protruding 2" above ground, set firmly, Steel post North 1.0 ft

53" Fir N.65°W. 38.3' to ctr. w/chopped-out blaze

23" Hemlock stump N.28°E. 137.0' to ctr. Painted

22" Hemlock stump S.76½°E. 113.5' to ctr. Painted

New BTs- 8" D.Fir, N.62°E., 14.3 ft. to ctr. blazed & scribed "T25S R2W S8 BT" continued next pg

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

8" D.Fir, S.71°E., 35.4 ft. to ctr. blazed & scribed "T25S R2W S17 BT"
9" D.Fir S.80°W., 12.3 ft. to ctr. Blazed & scribed "T25S R2W S18 BT"

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCS0 records Vol. 57 Page(s) 22795-6

The cor. of secs. 7, 8, 17, & 18, perpetuated by Christensen, in 1999, monumented with an iron post, 2½" dia., firmly set, flush with the ground, with brass cap (properly) mkd. from which the remains of original bearing trees
A decayed hemlock stump, size indeterminate, bears N.18°E., 19.1 ft., with fragmentary scribe marks visible on blazed fragment lying alongside.
A sawed fir stump, 48" dia., bears S.51°W., 54.1 ft., with scribe marks 2W 8 BT visible on open double blaze.
A fir, 53" dia., bears N.64°W., 39.6 ft., with a healed blaze.
and the remains of bearing trees mkd. by Hosford, in 1957
A sawed, decayed cedar stump, 48" dia., bears N.4°E., 58.7 ft., with scribe marks S8 253 visible on a partially healed blaze.
A fir stump, 60" dia., bears S.54°E., 54.1 ft., with no marks visible.
A decayed hemlock stump, size indeterminate, bears S.30¾°W., 109.6 ft., with no marks visible. (Record, S.32½°W.)
and bearing trees mkd. by Brooks
A decayed hemlock snag, 15" dia., bears N.28°E., 134.9 ft., with no marks visible. (Record, 137.3 ft.)
A hemlock snag, 24" dia., bears S.77½°E., 113.5 ft with no mks visible on a partially healed blaze. (Rec S.76½°E.)
and the remains of bearing trees mkd. by Christensen
A fir, 11" dia., bears N.57½°E., 14.2 ft., with a healed blaze.
A roothole bears S.76¾°E., 35.9 ft., alongside of which is a fir trunk, 9" dia., with a healed blaze.
A fir, 12" dia., bears S.77¾°W., 12.0 ft., with a healed blaze.
and a new bearing tree
A fir, 12" dia., bears S.59¾°E., 38.9 ft., mkd. T25S R2W S17 BT.
NAD 1983 (CORS 96)
Latitude: 43°24'09.08"N. Longitude: 122°58'21.40"W.

Fd as per rec. by R. Quimby, 2/2014 - M167-34 A&B

continued next page

TOWNSHIP 25 RANGE 02 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 1/27/2026 - C.S. File 67/62-05

Found - 3/4" 1962 BLM brass cap. Hosfords 1 1/2" I.P. on South side.

T25S R2W
S 7 | S 8
S 18 | S 17
1962

Decayed Hemlock stump N.18°E. 19.1 ft. size
indeterminate under 34" log.
Very rotted, burned 36" x 3 ft. fir stump S.51°W.
54.1 ft. No visible marks.
Burned - dead 57" D. Fir N.64°W. 37.8 ft. (Rec
39.6 ft.) No marks visible. Add 3 1/2" mag nail
right side center.
Sawn - decayed 48" cedar stump N.4°E. 58.7 ft. Rec
not checked due to brush.
Very rotted, burned 50" fir stump S.54°E. 54.1 ft.
Sawn - burnt 14" x 1 1/2 ft. fir stump N.57 1/2°E. 14.2
ft. healed blaze. Add 3 1/2" mag nail top center.
Burned - dead 13" fir S.77 3/4°W. 12.0 ft. healed
single blaze. Add 3 1/2" mag nail right side center.
Burnt - dead 14" D. Fir S.59°E. 38.6 ft (Rec S.59 3/4°E.
38.9 ft.) fully healed single blaze. Add 3 1/2" mag
nail right side center.

New - Burnt - sawn 19" x 1 1/2 ft. hemlock stump N.75°E.
16.5 ft. 3 1/2" mag nail top center.

Notes - Mon. 450± North of gravel road.
Area burnt 9/2020
Mon. On m/l flat ground. Burned forest N.W. and
S.E. quad. Rest clearcut.

Compass decl. 14 1/4°E.
TRIMBLE GEO XT LOCATION
43.40252164° N.
122.97263702° W.